



Council of the
European Union

Brussels, 4 June 2019
(OR. en)

9340/19

Interinstitutional File:
2019/0106 (NLE)

UD 139

LEGISLATIVE ACTS AND OTHER INSTRUMENTS

| | |
|----------|---|
| Subject: | COUNCIL REGULATION amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products |
|----------|---|

COUNCIL REGULATION (EU) 2019/...

of ...

**amending Regulation (EU) No 1387/2013
suspending the autonomous Common Customs Tariff duties
on certain agricultural and industrial products**

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) In order to ensure a sufficient and uninterrupted supply of certain agricultural and industrial products which are unavailable in the Union and thereby avoid any disturbances on the market for those products, autonomous Common Customs Tariff ('CCT') duties on those products have been suspended by Council Regulation (EU) No 1387/2013¹. Those products can be imported into the Union at reduced or zero duty rates.
- (2) The Union production of 97 products that are not listed in the Annex to Regulation (EU) No 1387/2013 is inadequate or non-existent. It is therefore in the interest of the Union to suspend totally the autonomous CCT duties on those products.
- (3) It is necessary to modify the conditions for the suspension of autonomous CCT duties for 47 products listed in the Annex to Regulation (EU) No 1387/2013 in order to take into account technical product developments and economic trends on the market.

¹ Council Regulation (EU) No 1387/2013 of 17 December 2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products and repealing Regulation (EU) No 1344/2011 (OJ L 354, 28.12.2013, p. 201).

- (4) It is no longer in the interest of the Union to maintain the suspension of autonomous CCT duties for 26 of the products that are listed in the Annex to Regulation (EU) No 1387/2013. The suspensions for those products should therefore be deleted. Moreover, with a view to promoting integrated battery production in the Union and in accordance with the communication from the Commission entitled 'Europe on the Move - Sustainable Mobility for Europe: safe, connected, and clean', the suspensions for 20 additional products listed in that Annex should be withdrawn. Furthermore, another 50 suspensions should be deleted from that Annex as a result of the implementation of the agreement in the form of the Declaration on the Expansion of Trade in Information Technology Products¹, which reduced the duty rate for the products concerned to zero.
- (5) Regulation (EU) No 1387/2013 should therefore be amended accordingly.
- (6) In order to avoid any interruption of the application of the autonomous suspension scheme and to comply with the guidelines set out in the communication from the Commission concerning autonomous tariff suspensions and quotas², the changes provided for in this Regulation regarding the tariff suspensions for the products concerned should apply from 1 July 2019. This Regulation should therefore enter into force as a matter of urgency,

HAS ADOPTED THIS REGULATION:

¹ OJ L 161, 18.6.2016, p. 4.

² OJ C 363, 13.12.2011, p. 6.

Article 1

The Annex to Regulation (EU) No 1387/2013 is amended as follows:

- (1) all asterisks in the table and the endnote (*), containing the text 'New or amended position or position with prolonged validity.', are deleted;
- (2) in the table, the rows for the products for which the CN and TARIC codes are set out in Annex I to this Regulation are deleted;
- (3) the rows for the products listed in Annex II to this Regulation are inserted into the table according to the order of the CN and TARIC codes indicated in the first and second columns of that table, respectively.

Article 2

This Regulation shall enter into force on the date of its publication in the *Official Journal of the European Union*.

It shall apply from 1 July 2019.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at ...,

For the Council

The President

ANNEX I

In the table set out in the Annex to Regulation (EU) No 1387/2013, the rows relating to suspensions for the products identified by the following CN and TARIC codes are deleted:

| CN code | TARIC |
|---------------|-------|
| ex 2826 90 80 | 10 |
| ex 2826 90 80 | 20 |
| ex 2920 90 10 | 15 |
| ex 2920 90 10 | 25 |
| ex 2920 90 10 | 35 |
| ex 2921 19 99 | 25 |
| ex 2926 90 70 | 12 |
| ex 3208 90 19 | 20 |
| ex 3506 91 10 | 10 |
| ex 3506 91 10 | 40 |
| ex 3506 91 10 | 50 |
| ex 3506 91 90 | 10 |
| ex 3506 91 90 | 40 |
| ex 3506 91 90 | 50 |
| ex 3506 91 90 | 60 |
| ex 3701 30 00 | 20 |
| ex 3701 30 00 | 30 |
| ex 3701 99 00 | 10 |
| ex 3707 90 29 | 10 |
| ex 3707 90 29 | 40 |
| ex 3707 90 29 | 50 |
| ex 3801 10 00 | 10 |

| CN code | TARIC |
|---------------|-------|
| ex 3801 90 00 | 30 |
| ex 3806 90 00 | 10 |
| ex 3812 39 90 | 35 |
| ex 3815 19 90 | 87 |
| ex 3815 90 90 | 22 |
| ex 3824 99 92 | 37 |
| ex 3904 10 00 | 20 |
| ex 3907 20 20 | 40 |
| ex 3909 40 00 | 60 |
| ex 3921 19 00 | 35 |
| ex 3921 19 00 | 40 |
| ex 5603 12 90 | 50 |
| ex 5603 12 90 | 70 |
| ex 5603 13 90 | 70 |
| ex 5603 92 90 | 40 |
| ex 5603 93 90 | 10 |
| ex 7410 11 00 | 10 |
| ex 8108 20 00 | 40 |
| ex 8108 20 00 | 60 |
| ex 8467 99 00 | 10 |
| ex 8479 89 97 | 50 |
| ex 8479 89 97 | 80 |
| ex 8479 90 20 | 80 |
| ex 8479 90 70 | 80 |
| ex 8481 80 59 | 30 |
| ex 8481 80 59 | 40 |
| ex 8481 80 59 | 50 |
| ex 8481 80 59 | 60 |

| CN code | TARIC |
|---------------|-------|
| ex 8482 10 10 | 40 |
| ex 8482 10 90 | 30 |
| ex 8501 31 00 | 55 |
| ex 8501 32 00 | 60 |
| ex 8501 33 00 | 15 |
| ex 8504 40 82 | 40 |
| ex 8504 40 82 | 50 |
| ex 8504 40 88 | 30 |
| ex 8504 40 90 | 15 |
| ex 8504 40 90 | 25 |
| ex 8504 40 90 | 30 |
| ex 8504 40 90 | 40 |
| ex 8504 40 90 | 50 |
| ex 8504 40 90 | 70 |
| ex 8504 40 90 | 80 |
| ex 8504 50 95 | 20 |
| ex 8504 50 95 | 40 |
| ex 8504 50 95 | 50 |
| ex 8504 50 95 | 60 |
| ex 8504 50 95 | 70 |
| ex 8504 50 95 | 80 |
| ex 8504 90 11 | 10 |
| ex 8504 90 11 | 20 |
| ex 8504 90 99 | 20 |
| ex 8506 90 00 | 10 |
| ex 8507 10 20 | 80 |
| ex 8507 50 00 | 20 |

| CN code | TARIC |
|---------------|-------|
| ex 8507 50 00 | 40 |
| ex 8507 60 00 | 15 |
| ex 8507 60 00 | 20 |
| ex 8507 60 00 | 23 |
| ex 8507 60 00 | 25 |
| ex 8507 60 00 | 30 |
| ex 8507 60 00 | 33 |
| ex 8507 60 00 | 43 |
| ex 8507 60 00 | 45 |
| ex 8507 60 00 | 47 |
| ex 8507 60 00 | 50 |
| ex 8507 60 00 | 53 |
| ex 8507 60 00 | 60 |
| ex 8507 60 00 | 71 |
| ex 8507 60 00 | 80 |
| ex 8507 60 00 | 85 |
| ex 8507 80 00 | 20 |
| ex 8507 90 80 | 60 |
| ex 8518 29 95 | 30 |
| ex 8518 29 95 | 40 |
| ex 8518 30 95 | 20 |
| ex 8518 40 80 | 91 |
| ex 8518 40 80 | 92 |
| ex 8518 40 80 | 93 |
| ex 8518 90 00 | 30 |
| ex 8518 90 00 | 35 |
| ex 8518 90 00 | 40 |

| CN code | TARIC |
|---------------|-------|
| ex 8518 90 00 | 50 |
| ex 8518 90 00 | 60 |
| ex 8518 90 00 | 80 |
| ex 8522 90 49 | 60 |
| ex 8522 90 49 | 65 |
| ex 8522 90 80 | 30 |
| ex 8522 90 80 | 65 |
| ex 8522 90 80 | 80 |
| ex 8522 90 80 | 84 |
| ex 8522 90 80 | 97 |
| ex 8526 10 00 | 20 |
| ex 8527 99 00 | 10 |
| ex 8527 99 00 | 20 |
| ex 8529 10 80 | 60 |
| ex 8529 10 80 | 70 |
| ex 8529 90 65 | 15 |
| ex 8529 90 65 | 25 |
| ex 8529 90 65 | 40 |
| ex 8529 90 92 | 57 |
| ex 8535 90 00 | 30 |
| ex 8536 49 00 | 30 |
| ex 8536 50 11 | 35 |
| ex 8536 50 11 | 40 |
| ex 8536 50 19 | 93 |
| ex 8536 50 80 | 81 |
| ex 8536 50 80 | 82 |
| ex 8536 50 80 | 83 |
| ex 8536 50 80 | 97 |

| CN code | TARIC |
|---------------|-------|
| ex 8545 90 90 | 30 |
| ex 9001 20 00 | 10 |
| ex 9001 20 00 | 20 |
| ex 9001 90 00 | 55 |
| ex 9002 11 00 | 15 |
| ex 9002 11 00 | 25 |
| ex 9002 11 00 | 35 |
| ex 9002 11 00 | 45 |
| ex 9002 11 00 | 55 |
| ex 9002 11 00 | 65 |
| ex 9002 11 00 | 75 |
| ex 9002 19 00 | 10 |
| ex 9002 19 00 | 20 |
| ex 9002 19 00 | 30 |
| ex 9002 19 00 | 40 |
| ex 9002 19 00 | 50 |
| ex 9002 19 00 | 60 |
| ex 9002 19 00 | 70 |
| ex 9027 10 90 | 10 |
| ex 9029 20 31 | 10 |
| ex 9029 90 00 | 20 |
| ex 9030 31 00 | 20 |

ANNEX II

In the table set out in the Annex to Regulation (EU) No 1387/2013, the following rows are inserted according to the order of the CN and TARIC codes indicated in the first and second columns of that table, respectively:

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 1516 20 10 | | Hydrogenated castor oil, so called 'opal-wax' | 0 % | - | 31.12.2023 |
| ex 2818 10 11 | 10 | Sol-Gel corundum (CAS RN 1302-74-5) with an aluminium oxide content of 99,6 % or more by weight, having a micro crystalline structure in the form of rods with an aspect ratio of 1,3 or more, but not more than 6,0 | 0 % | - | 31.12.2023 |
| ex 2826 90 80 | 10 | Lithium hexafluorophosphate (1-) (CAS RN 21324-40-3) | 0 % | - | 31.12.2019 |
| ex 2828 10 00 | 10 | Calcium hypochlorite (CAS RN 7778-54-3) having an active chlorine content of 65 % or more | 0 % | - | 31.12.2023 |
| ex 2905 32 00 | 10 | (2S)-propane-1,2-diol (CAS RN 4254-15-3) | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 2909 30 90 | 35 | 1-Chloro-2-(4-ethoxybenzyl)-4-iodobenzene (CAS RN 1103738-29-9) | 0 % | - | 31.12.2023 |
| ex 2910 90 00 | 25 | Phenyloxirane (CAS RN 96-09-3) | 0 % | - | 31.12.2023 |
| ex 2912 29 00 | 55 | Cyclohex-3-ene-1-carbaldehyde (CAS RN 100-50-5) | 0 % | - | 31.12.2023 |
| ex 2915 90 70 | 15 | 2,2-Dimethylbutanoyl chloride (CAS RN 5856-77-9) | 0 % | - | 31.12.2023 |
| ex 2916 39 90 | 57 | 2-Phenylprop-2-enoic acid (CAS RN 492-38-6) | 0 % | - | 31.12.2023 |
| ex 2918 30 00 | 25 | (E)-1-ethoxy-3-oxobut-1-en-1-olate; 2-methylpropan-1-olate; titanium(4+) (CAS RN 83877-91-2) | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 2918 99 90 | 33 | Vanillic Acid (CAS RN 121-34-6) containing – not more than 10 ppm of Palladium (CAS RN 7440-05-3), – not more than 10 ppm of bismuth (CAS RN 7440-69-9), – not more than 14 ppm of formaldehyde (CAS RN 50-00-0), – not more than 1,3 % by weight of 3,4-dihydroxybenzoic acid (CAS RN 99-50-3), – not more than 0,5 % by weight of vanillin (CAS RN 121-33-5) | 0 % | - | 31.12.2023 |
| ex 2920 90 10 | 15 | Ethyl methyl carbonate (CAS RN 623-53-0) | 0 % | - | 31.12.2019 |
| ex 2920 90 10 | 25 | Diethyl carbonate (CAS RN 105-58-8) | 0 % | - | 31.12.2019 |
| ex 2920 90 10 | 35 | Vinylene carbonate (CAS RN 872-36-6) | 0 % | - | 31.12.2019 |
| ex 2920 90 70 | 20 | Diethyl phosphorochloridate (CAS RN 814-49-3) | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 2921 43 00 | 70 | 5-Bromo-4-fluoro-2-methylaniline (CAS RN 627871-16-3) | 0 % | - | 31.12.2023 |
| ex 2921 45 00 | 30 | (5 or 8)-Aminonaphthalene-2-sulphonic acid (CAS RN 51548-48-2) | 0 % | - | 31.12.2023 |
| ex 2921 45 00 | 80 | 2-Aminonaphthalene-1-sulphonic acid (CAS RN 81-16-3) | 0 % | - | 31.12.2023 |
| ex 2921 49 00 | 35 | 2-Ethylaniline (CAS RN 578-54-1) | 0 % | - | 31.12.2023 |
| ex 2922 19 00 | 55 | 3-Aminoadamantan-1-ol (CAS RN 702-82-9) | 0 % | - | 31.12.2023 |
| ex 2922 29 00 | 33 | o-Phenetidine (CAS RN 94-70-2) | 0 % | - | 31.12.2023 |
| ex 2923 90 00 | 65 | N,N,N-trimethyl-tricyclo[3.3.1.1 ^{3,7}]decan-1-aminium hydroxide (CAS RN 53075-09-5) in form of an aqueous solution with a content of N,N,N-trimethyl-tricyclo[3.3.1.1 ^{3,7}]decan-1-aminium hydroxide by weight of 17,5 % or more but not more than 27,5 % | 0 % | - | 31.12.2023 |
| ex 2924 19 00 | 75 | (S)-4-((tert-Butoxycarbonyl)amino)-2-hydroxybutanoic acid (CAS RN 207305-60-0) | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 2924 29 70 | 67 | N,N'-(2,5-Dichloro-1,4-phenylene)bis[3-oxobutyramide] (CAS RN 42487-09-2) | 0 % | - | 31.12.2023 |
| ex 2924 29 70 | 70 | N-[(benzyloxy)carbonyl]glycyl-N-[(2S)-1-{4-[(tert-butoxycarbonyl)oxy]phenyl}-3-hydroxypropan-2-yl]-L-alaninamide | 0 % | - | 31.12.2023 |
| ex 2926 90 70 | 60 | Cyfluthrin (ISO) (CAS RN 68359-37-5) or beta-cyfluthrin (ISO) (CAS RN 1820573-27-0) with a purity by weight of 95 % or more | 0 % | - | 31.12.2019 |
| ex 2930 90 98 | 38 | Allyl isothiocyanate (CAS RN 57-06-7) | 0 % | - | 31.12.2023 |
| ex 2930 90 98 | 50 | 3-Mercaptopropionic acid (CAS RN 107-96-0) | 0 % | - | 31.12.2023 |
| ex 2932 19 00 | 65 | Tefuryltrione (ISO) (CAS RN 473278-76-1) | 0 % | - | 31.12.2023 |
| ex 2932 20 90 | 75 | 3-Acetyl-6-methyl-2 <i>H</i> -pyran-2, 4(3 <i>H</i>)-dione (CAS RN 520-45-6) | 0 % | - | 31.12.2023 |
| ex 2932 99 00 | 27 | (2-Butyl-3-benzofuranyl)(4-hydroxy-3,5-diiodophenyl)methanone (CAS RN 1951-26-4) | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 2933 19 90 | 65 | 4-Bromo-1-(1-ethoxyethyl)-1H-pyrazole (CAS RN 1024120-52-2) | 0 % | - | 31.12.2023 |
| ex 2933 39 99 | 56 | 2,5-Dichloro-4,6-dimethylnicotinonitrile (CAS RN 91591-63-8) | 0 % | - | 31.12.2023 |
| ex 2933 39 99 | 59 | Chlorpyrifos-Methyl (ISO) (CAS RN 5598-13-0) | 0 % | - | 31.12.2023 |
| ex 2933 39 99 | 61 | 6-Bromopyridin-2-amine (CAS RN 19798-81-3) | 0 % | - | 31.12.2023 |
| ex 2933 39 99 | 62 | Ethyl 2,6-Dichloronicotinate (CAS RN 58584-86-4) | 0 % | - | 31.12.2023 |
| ex 2933 39 99 | 64 | Methyl 1-(3-chloropyridin-2-yl)-3-hydroxymethyl-1H-pyrazole-5-carboxylate (CAS RN 960316-73-8) | 0 % | - | 31.12.2023 |
| ex 2933 39 99 | 68 | 1-(3-Chloropyridin-2-yl)-3-[[5-(trifluoromethyl)-2H-tetrazol-2-yl]methyl]-1H-pyrazole-5-carboxylic acid (CAS RN 1352319-02-8) with a purity by weight of 85 % or more | 0 % | - | 31.12.2023 |
| ex 2933 49 90 | 80 | Ethyl 6,7,8-trifluoro-1-[formyl(methyl)amino]-4-oxo-1,4-dihydroquinoline-3-carboxylate (CAS RN 100276-65-1) | 0 % | - | 31.12.2020 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 2933 54 00 | 10 | 5,5'-(1,2-diazenediyl)bis [2,4,6 (1H, 3H, 5H)-pyrimidinetrione] (CAS RN 25157-64-6) | 0 % | - | 31.12.2023 |
| ex 2933 59 95 | 63 | 1-(3-Chlorophenyl) piperazine (CAS RN 6640-24-0) | 0 % | - | 31.12.2023 |
| ex 2933 69 80 | 27 | Troclosene sodium dihydrate (INN) (CAS RN 51580-86-0) | 0 % | - | 31.12.2023 |
| ex 2933 99 80 | 58 | Ipconazole (ISO) (CAS RN 125225-28-7) with a purity by weight of 90 % or more | 0 % | - | 31.12.2023 |
| ex 2933 99 80 | 59 | Hydrates of Hydroxybenzotriazole (CAS RN 80029-43-2 and CAS RN 123333-53-9) | 0 % | - | 31.12.2023 |
| ex 2933 99 80 | 61 | (1R,5S)-8-Benzyl-8-azabicyclo(3.2.1)octan-3-one hydrochloride (CAS RN 83393-23-1) | 0 % | - | 31.12.2023 |
| ex 2933 99 80 | 63 | L-Prolinamide (CAS RN 7531-52-4) | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 2933 99 80 | 68 | 5-((1S,2S)-2-((2R,6S,9S,11R,12R,14aS,15S,16S,20R,23S,25aR)-9-amino-20-((R)-3-amino-1-hydroxy-3-oxopropyl)-2,11,12,15-tetrahydroxy-6-((R)-1-hydroxyethyl)-16-methyl-5,8,14,19,22,25-hexaoxotetracosahydro-1H-dipyrrolo[2,1-c:2',1'-l][1,4,7,10,13,16]hexaazacyclohenicosin-23-yl)-1,2-dihydroxyethyl)-2-hydroxyphenyl hydrogen sulphate (CAS RN 168110-44-9) | 0 % | - | 31.12.2023 |
| ex 2934 99 90 | 78 | [(3aS,5R,6S,6aS)-6-Hydroxy-2,2-dimethyltetrahydrofuro[2,3-d][1,3]dioxol-5-yl] (morpholino)methanone (CAS RN 1103738-19-7) | 0 % | - | 31.12.2023 |
| ex 2934 99 90 | 80 | 2-(dimethylamino)-2-[(4-methylphenyl)methyl]-1-[4-(morpholin-4-yl)phenyl]butan-1-one (CAS RN 119344-86-4) | 0 % | - | 31.12.2023 |
| ex 2935 90 90 | 33 | 4-Chloro-3-pyridinesulphonamide (CAS RN 33263-43-3) | 0 % | - | 31.12.2023 |
| ex 2935 90 90 | 37 | 1,3-Dimethyl-1H-pyrazole-4-sulfonamide (CAS RN 88398-53-2) | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 2935 90 90 | 60 | 4-[(3-Methylphenyl)amino]pyridine-3-sulphonamide (CAS RN72811-73-5) | 0 % | - | 31.12.2023 |
| ex 3204 17 00 | 31 | Colourant C.I. Pigment Red 63:1 (CAS RN 6417-83-0) and preparations based thereon with a colourant C.I. Pigment Red 63:1 content of 70 % or more by weight | 0 % | - | 31.12.2023 |
| ex 3205 00 00 | 20 | <p>Colourant C.I. Solvent Red 48 (CAS RN 13473-26-2) preparation, in a form of dry powder, containing by weight:</p> <ul style="list-style-type: none"> – 16 % or more but not more than 25 % of Colourant C.I. Solvent Red 48 (CAS RN 13473-26-2), – 65 % or more but no more than 75 % of aluminium hydroxide (CAS RN 21645-51-2) | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 3205 00 00 | 30 | <p>Colourant C.I. Pigment Red 174 (CAS RN 15876-58-1) preparation, in a form of dry powder, containing by weight:</p> <ul style="list-style-type: none"> – 16 % or more but not more than 21 % of Colourant C.I. Pigment Red 174 (CAS RN 15876-58-1), – 65 % or more but no more than 69 % of aluminium hydroxide (CAS RN 21645-51-2) | 0 % | - | 31.12.2023 |
| ex 3208 90 19 | 55 | Preparation of 5 % or more but not more than 20 % by weight of a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene, isobutene and maleic anhydride in an organic solvent | 0 % | - | 31.12.2020 |
| ex 3506 91 90 | 10 | Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA) | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 3506 91 90 | 40 | Acrylic pressure sensitive adhesive with a thickness of 0,076 mm or more but not more than 0,127 mm, put up in rolls of a width of 45,7 cm or more but not more than 132 cm supplied on a release liner with an initial peel adhesion release value of not less than 15 N/25 mm (measured according to ASTM D3330) | 0 % | - | 31.12.2019 |
| ex 3506 91 90 | 50 | Preparation containing by weight: <ul style="list-style-type: none"> – 15 % or more but not more than 60 % of styrene butadiene copolymers or styrene isoprene copolymers, and – 10 % or more but not more than 30 % of pinene polymers or pentadiene copolymers, dissolved in: <ul style="list-style-type: none"> – Methyl ethyl ketone (CAS RN 78-93-3), – Heptane (CAS RN 142-82-5), and – Toluene (CAS RN 108-88-3) or light aliphatic solvent naphtha (CAS RN 64742-89-8) | 0 % | - | 31.12.2020 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 3506 91 90 | 60 | Temporary wafer-bonding adhesive material in the form of a suspension of a solid polymer in D-limonene (CAS RN 5989-27-5) with a polymeric content by weight of 25 % or more but not more than 35 % | 0 % | 1 | 31.12.2022 |
| ex 3812 39 90 | 35 | Mixture containing by weight: <ul style="list-style-type: none"> – 25 % or more but not more than 55 % of a mixture of C15-18 tetramethylpiperidiny l esters (CAS RN 86403-32-9), – not more than 20 % of other organic compounds, – on a carrier of polypropylene (CAS RN 9003-07-0) or amorphous silica (CAS RN 7631-86-9 or 112926-00-8) | 0 % | - | 31.12.2023 |
| ex 3815 12 00 | 20 | Spherical catalyst consisting of a support of aluminium oxide coated with platinum, with <ul style="list-style-type: none"> – a diameter of 1,4 mm or more but not more than 2,0 mm, and – a platinum content by weight of 0,2 % or more but not more than 0,5 % | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 3815 12 00 | 30 | <p>Catalyst</p> <ul style="list-style-type: none"> – containing 0,3 gram per litre or more, but not more than 7 gram per litre of precious metals, – deposited on a ceramic honeycomb structure coated with aluminium oxide or cerium/zirconium oxide, the honeycomb structure having, – a nickel content of 1,26 % by weight or more, but not more than 1,29 % by weight, – 62 cells per cm² or more, but not more than 140 cells per cm², – a diameter of 100 mm or more, but not more than 120 mm, and – a length of 60 mm or more, but not more than 150 mm, <p>for use in the production of motor vehicles⁽²⁾</p> | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 3815 90 90 | 43 | Catalyst in powder form consisting by weight of – 92,50 % (\pm 2) % titanium dioxide (CAS RN 13463-67-7), – 5 % (\pm 1) % silicon dioxide (CAS RN 112926-00-8), and – 2,5 % (\pm 1,5) % sulphur trioxide (CAS RN 7446-11-9) | 0 % | - | 31.12.2022 |
| ex 3824 99 92 | 31 | Liquid crystal mixtures for use in the manufacture of LCD (liquid crystal display) modules ⁽²⁾ | 0 % | - | 31.12.2023 |
| ex 3824 99 92 | 37 | Mixture of acetates of 3-butene-1,2-diol with a content by weight of 65 % or more of 3-butene-1,2-diol diacetate (CAS RN 18085-02-4) | 0 % | - | 31.12.2023 |
| ex 3824 99 96 | 33 | Buffer cartridge not exceeding 8000 ml containing: – 0,05 % or more but not more than 0,1 % by weight of 5-Chloro-2-methyl-2,3-dihydroisothiazol-3-one (CAS RN 55965-84-9), and – 0,05 % or more but not more than 0,1 % by weight of 2-Methyl-2,3-dihydroisothiazol-3-one (CAS RN 2682-20-4) as a biostatic | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 3904 69 80 | 20 | Copolymer of tetrafluoroethylene, heptafluoro-1-pentene and ethene (CAS RN 94228-79-2) | 0 % | - | 31.12.2023 |
| ex 3904 69 80 | 30 | Copolymer of tetrafluoroethylene, hexafluoropropene and ethene | 0 % | - | 31.12.2023 |
| ex 3907 20 20 | 40 | Copolymer of tetrahydrofuran and tetrahydro-3-methylfuran with a number average molecular weight (Mn) of 900 or more but not more than 3 600 | 0 % | - | 31.12.2023 |
| ex 3920 99 59 | 30 | Poly(tetrafluoroethylene) film containing by weight 10 % or more of graphite | 0 % | - | 31.12.2023 |
| ex 3921 19 00 | 40 | Transparent, microporous, acrylic acid grafted polyethylene film, in the form of rolls, with: <ul style="list-style-type: none"> – a width of 98 mm or more but not more than 170 mm, – a thickness of 15 µm or more but not more than 36 µm, of a kind used for the manufacture of alkaline battery separators | 0 % | - | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 3926 30 00 | 40 | Plastic internal door handle used in the manufacture of motor vehicles ⁽²⁾ | 0 % | - | 31.12.2023 |
| ex 5402 44 00 | 10 | Synthetic elastomeric filament yarn: – untwisted or with a twist not exceeding 50 turns per metre, measuring 300 dtex or more but not more than 1000 dtex, – composed of polyurethane ureas based on a copolyether glycol of tetrahydrofuran and 3-methyltetrahydrofuran, for use in the manufacture of disposable hygiene products of heading 9619 ⁽²⁾ | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 7006 00 90 | 40 | Plates of sodalime glass of STN (Super Twisted Nematic) quality having: <ul style="list-style-type: none"> – a length of 300 mm or more but not more than 600 mm, – a width of 300 mm or more but not more than 600 mm, – a thickness of 0,5 mm or more but not more than 1,1 mm, – an indium-tin-oxide coating with a resistance of 80 Ohms or more, but not more than 160 Ohms on one side, – a multi layer anti-reflection-coating on the other side, and – machined (chamfered) edges, of a kind used in the manufacture of LCD (liquid crystal display) modules | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| ex 7019 40 00 ex 7019 52 00 | 70 30 | E-fibre glass fabrics: <ul style="list-style-type: none"> – having a weight of 20 g/m² or more, but not more than 214 g/m², – impregnated with silane, – in rolls, – having a humidity content by weight of 0,13 % or less, and – having not more than 3 hollow fibres out of 100 000 fibres, for the exclusive use in the manufacture of prepregs and copper clad laminates ⁽²⁾ | 0 % | - | 31.12.2021 |
| ex 7019 52 00 | 40 | Epoxy resin coated glass woven fabric containing by weight: <ul style="list-style-type: none"> – 91 % or more but not more than 93 % of glass fibres, – 7 % or more but not more than 9 % of epoxy resin | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 7410 11 00 | 10 | Roll of laminate foil of graphite and copper, with: | 0 % | - | 31.12.2019 |
| ex 8507 90 80 | 60 | – a width of 610 mm or more but not more than 620 mm, and | | | |
| ex 8545 90 90 | 30 | – a diameter of 690 mm or more but not more than 710 mm, for use in the manufacture of lithium-ion electric rechargeable batteries ⁽²⁾ | | | |
| ex 7607 20 90 | 10 | Aluminium foil, in rolls: – coated with polypropylene on one side and with polyamide on the other side with adhesive layers between, – with a width of 200 mm or more, but not more than 400 mm, – with a thickness of 0,138 mm or more, but not more than 0,168 mm, for use in the manufacture of lithium-ion battery cell pouches ⁽²⁾ | 0 % | - | 31.12.2019 |
| 8104 11 00 | | Unwrought magnesium, containing at least 99,8 % by weight of magnesium | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8108 20 00 | 40 | <p>Titanium alloy ingot,</p> <ul style="list-style-type: none"> – with a height of 17,8 cm or more, a length of 180 cm or more and a width of 48,3cm or more, – a weight of 680 kg or more, <p>containing alloy elements by weight of:</p> <ul style="list-style-type: none"> – 3 % or more but not more than 6 % of aluminium, – 2,5 % or more but not more than 5 % of tin, – 2,5 % or more but not more than 4,5 % of zirconium, – 0,2 % or more but not more than 1 % of niobium, – 0,1 % or more but not more than 1 % of molybdenum, – 0,1 % or more but not more than 0,5 % of silicon | 0 % | p/st | 31.12.2020 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8108 20 00 | 60 | <p>Titanium alloy ingot,</p> <ul style="list-style-type: none"> – with a diameter of 63,5 cm or more and a length of 450 cm or more, – a weight of 6 350 kg or more, <p>containing alloy elements by weight of:</p> <ul style="list-style-type: none"> – 5,5 % or more but not more than 6,7 % of aluminium, – 3,7 % of more but not more than 4,9 % of vanadium | 0 % | p/st | 31.12.2020 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8301 20 00 | 10 | <p>Mechanical or electromechanical steering column lock:</p> <ul style="list-style-type: none"> – with a height of 10,5 cm (\pm 3 cm), – with a width of 6,5 cm (\pm 3 cm), – in a metal housing, – whether or not with a holder, <p>for use in the manufacture of goods of Chapter 87⁽²⁾</p> | 0 % | - | 31.12.2023 |
| ex 8302 30 00 | 10 | <p>Support bracket for an exhaust system:</p> <ul style="list-style-type: none"> – with a thickness of 0,7 mm or more but not more than 1,3 mm, – of stainless steel class 1.4310 and 1.4301 according to norm EN 10088, – whether or not with mounting holes, <p>for use in the manufacture of exhaust systems for automobiles⁽²⁾</p> | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8409 91 00 | 60 | <p>The air intake module for engine cylinders consisting of:</p> <ul style="list-style-type: none"> – a suction pipe, – a pressure sensor, – an electric throttle, – hoses, – brackets, <p>for use in the manufacture of goods of Chapter 87⁽²⁾</p> | 0 % | - | 31.12.2023 |
| ex 8409 91 00 | 70 | <p>Inlet manifold, exclusively for use in the manufacture of the motor vehicles with:</p> <ul style="list-style-type: none"> – a width of 40 mm or more but not more than 70 mm, – valves length of 250 mm or more but not more than 350 mm, – air volume of 5,2 litres, and – an electrical flow control system that provides maximum performance at more than 3200 rpm⁽²⁾ | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8409 99 00 | 65 | <p>The exhaust gas recirculation assembly consisting of:</p> <ul style="list-style-type: none"> – a control unit, – an air throttle, – an intake pipe, – an outlet hose, <p>for use in the manufacture of diesel engines of motor vehicles⁽²⁾</p> | 0 % | - | 31.12.2023 |
| ex 8414 10 25 | 30 | <p>Tandem pump consisting of:</p> <ul style="list-style-type: none"> – an oil pump with displacement of 21,6 cc/rev (± 2 cc/rev) and working pressure 1,5 bar at 1 000 revolutions per minute, – vacuum pump with displacement of 120 cc/rev (± 12 cc/rev) and performance of -666 mbar in 6 seconds at 750 revolutions per minute, <p>for use in the manufacture of engines of motor vehicles⁽²⁾</p> | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8414 10 89 | 30 | Electric vacuum pump with: <ul style="list-style-type: none"> – Controller Area Network (CAN bus), – whether or not with a rubber hose, – a connecting cable with connector, – a mounting bracket, for use in the manufacture of goods of Chapter 87 ⁽²⁾ | 0 % | - | 31.12.2023 |
| ex 8414 30 89 | 30 | Open shaft, scroll type compressor with clutch assembly, of a power of more than 0,4 kW, for air conditioning in vehicles, for use in the manufacture of motor vehicles of Chapter 87 ⁽²⁾ | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8414 59 35 | 20 | <p>Radial fan, with:</p> <ul style="list-style-type: none"> – a dimension of 25mm (height) x 85mm (width) x 85mm (depth), – a weight of 120 g, – a rated voltage of 13,6 VDC (direct current voltage), – an operating voltage of 9 VDC or more but not more than 16 VDC (direct current voltage), – a rated current of 1,1 A (TYP), – a rated power of 15 W, – a rotation speed of 500 RPM (revolutions per minute) or more but not more than 4800 RPM (revolutions per minute) (free flow), – an air flow of not more than 17,5 litre/s, – an air pressure of not more than 16 mm H₂O \approx 157 Pa, | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| | | <ul style="list-style-type: none"> – an overall sound pressure of not more than 58 dB(A) at 4800 RPM (revolutions per minute), and with a FIN (Fan Interconnect Network) interface for communication with the heating and air-conditioning control unit used in car seat ventilation systems | | | |
| ex 8467 99 00 | 10 | Mechanical switches for connecting electrical circuits, with: <ul style="list-style-type: none"> – a voltage of 14,4 V or more but not more than 42 V, – an amperage of 10 A or more but not more than 42 A, for use in the manufacture of machines falling within heading 8467 ⁽²⁾ | 0 % | p/st | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8481 80 59 | 30 | Two-way flow control valve with housing, with: <ul style="list-style-type: none"> – at least 5, but not more than 10 outlet holes with at least 0,09 mm, but not more than 0,2 mm diameter, – at least 550 cm³/minute, but not more than 2000 cm³/minute flow rate, – at least 19, but not more than 300 MPa operating pressure | 0 % | - | 31.12.2022 |
| ex 8481 80 59 | 40 | Flow-control valve <ul style="list-style-type: none"> – made of steel, – with an outlet hole with a diameter of at least 0,1 mm, but not more than 0,3 mm, – with an inlet hole with a diameter of at least 0,4 mm, but not more than 1,3 mm, – with chromium nitride coating, – with a surface roughness of Rp 0,4 | 0 % | - | 31.12.2022 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8481 80 59 | 50 | Electromagnetic valve for quantity control with <ul style="list-style-type: none"> – a plunger, – a solenoid with a of coil resistance of at least 2,6 Ohm, but not more than 3 Ohm | 0 % | - | 31.12.2022 |
| ex 8481 80 59 | 60 | Electromagnetic valve for quantity control <ul style="list-style-type: none"> – with a solenoid with a coil resistance of at least 0,19 Ohm, but not more than 0,66 Ohm, and with an inductance of not more than 1 mH | 0 % | - | 31.12.2022 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| ex 8481 80 79 ex 8481 80 99 | 30 30 | Service Valve which suits for R410A or R32 gas while connecting indoor and outdoor units with: <ul style="list-style-type: none"> – a withstanding pressure of the valve body of 6,3 MPa, – a leakage ratio of less than 1,6 g/a, – an impurity ratio of less than 1,2 mg/PCS, – an airtight pressure of the valve body of 4,2 MPa, for use in the manufacture of air conditioners ⁽²⁾ | 0 % | - | 31.12.2023 |
| ex 8484 20 00 | 20 | Mechanical face sealing device made of two movable rings (one ceramic mating, having a thermal conductivity lower than 80W/Mk and the other carbon sliding), one spring and a nitrile sealant on the external side, of a kind used in manufacturing circulation pumps of cooling systems in motor vehicles | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8501 10 10 | 30 | <p>Motors for air pumps, with:</p> <ul style="list-style-type: none"> – operating voltage of 9 VDC or more but not more than 24 VDC, – operating temperature range of -40°C or more but not more than 80°C, – an output not exceeding 18 W, <p>for use in the manufacture of pneumatic support and ventilation systems for car seats⁽²⁾</p> | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| ex 8501 31 00 ex 8501 32 00 | 55 40 | DC motor with or without commutator, with <ul style="list-style-type: none"> – an external diameter of 24,2 mm or more, but not more than 140 mm, – a rated speed of 3300 rpm or more, but not more than 26200 rpm, – a rated supply voltage of 3,6 V or more, but not more than 230 V, – an output power of more than 37,5 W , but not more than 2400 W, – a free load current of not more than 20,1 A, – a maximum efficiency of 50 % or more, for driving hand-held power tools or lawn mowers | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8501 33 00 | 25 | AC traction motor of an output of 75 kW or more but not more than 375 kW, with: <ul style="list-style-type: none"> – a torque output of 200 Nm or more but not more than 400 Nm, – a power output of 50 kW or more but not more than 200 kW, and – a speed of not more than 15 000 rpm, for use in the manufacture of electric vehicles ⁽²⁾ | 0 % | - | 31.12.2019 |
| ex 8503 00 99 | 55 | Stator for brushless motor, with: <ul style="list-style-type: none"> – an internal diameter of 206,6 mm ($\pm 0,5$), – an external diameter of 265,0 mm ($\pm 0,2$), and – a width of 37,2 mm or more but not more than 47,8 mm, of a kind used in the manufacture of washing machine, washer-dryer or dryer equipped with direct drive drums | 0 % | p/st | 31.12.2020 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8506 90 00 | 10 | Cathode, in rolls, for air zinc button cell batteries (hearing aid batteries) ⁽²⁾ | 0 % | - | 31.12.2023 |
| ex 8507 60 00 | 13 | Prismatic lithium-ion electric accumulators with: <ul style="list-style-type: none"> – a width of 173,0 mm ($\pm 0,4$ mm), – a thickness of 45,0 mm ($\pm 0,4$ mm), – a height 125,0 mm ($\pm 0,3$ mm), – a nominal voltage of 3,67 V ($\pm 0,01$ V), and – a nominal capacity of 94 Ah and/or 120 Ah, for use in the manufacture of rechargeable electric vehicle batteries ⁽²⁾ | 0 % | - | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8507 60 00 | 15 | Cylindrical lithium-ion-accumulators or modules with: <ul style="list-style-type: none"> – a nominal capacity of 8,8 Ah or more, but not more than 18 Ah, – a nominal voltage of 36 V or more, but not more than 48 V, – a power of 300 Wh or more, but not more than 648 Wh, for use in the manufacture of electric bicycles ⁽²⁾ | 0 % | - | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8507 60 00 | 18 | <p>Rectangular lithium-ion polymer accumulator equipped with a battery management system and can-bus interface with:</p> <ul style="list-style-type: none"> – a length of not more than 1600 mm, – a width of not more than 448 mm, – a height of not more than 395 mm, – a weight of 125 kg or more but not more than 135 kg, – a nominal voltage of 280 V or more but not more than 400 V, – a nominal capacity of 9,7 Ah or more but not more than 10,35 Ah, – a charging voltage of 110 V or more but not more than 230 V, and – containing 6 modules with 90 cells or more but not more than 96 cells enclosed in a steel casing, <p>for use in the manufacture of vehicle capable of being charged by plugging to external source of electric power of heading 8703⁽²⁾</p> | 0 % | - | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8507 60 00 | 30 | Cylindrical lithium-ion accumulator or module, with a length of 63 mm or more and a diameter of 17,2 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries ⁽²⁾ | 0 % | - | 31.12.2019 |
| ex 8507 60 00 | 33 | Lithium-ion accumulator, with: <ul style="list-style-type: none"> – a length of 150 mm or more, but not more than 1 000 mm, – a width of 100 mm or more, but not more than 1 000 mm, – a height of 200 mm or more, but not more than 1 500 mm, – a weight of 75 kg or more, but not more than 200 kg, – a nominal capacity not less than 150 Ah and not more than 500 Ah | 0 % | - | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8507 60 00 | 50 | <p>Modules for the assembly of batteries of ion lithium electric accumulators with:</p> <ul style="list-style-type: none"> – a length of 298 mm or more, but not more than 408 mm, – a width of 33,5 mm or more, but not more than 209 mm, – a height of 138 mm or more, but not more than 228 mm, – a weight of 3,6 kg or more, but not more than 17 kg, and – a power of 458 Wh or more, but not more than 2 158 Wh | 0 % | - | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8507 60 00 | 71 | Lithium-ion rechargeable batteries, with: <ul style="list-style-type: none"> – a length of 700 mm or more, but not more than 2 820 mm, – a width of 935 mm or more, but not more than 1 660 mm, – a height of 85 mm or more, but not more than 700 mm, – a weight of 250 kg or more, but not more than 700 kg, – a power of not more than 175 kWh | 0 % | - | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8507 60 00 | 85 | Lithium-ion Rectangular modules for incorporation in lithium-ion rechargeable batteries: <ul style="list-style-type: none"> – of a length of 300 mm or more, but not more than 350 mm, – of a width of 79,8 mm or more, but not more than 225 mm, – of a height of 35 mm or more, but not more than 168 mm, – of a weight of 3,95 kg or more, but not more than 8,85 kg, – with a rating of 66,6 Ah or more, but not more than 129 Ah | 0 % | - | 31.12.2019 |
| ex 8507 90 30 | 20 | Safety Reinforced Separator designed to separate cathode and anode in lithium-ion electric accumulators for use in the manufacture of lithium-ion electric accumulators for motor vehicle batteries ⁽²⁾ | 0 % | - | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8529 90 65 | 25 | Printed circuit board assembly comprising: <ul style="list-style-type: none"> – a radio tuner (capable of receiving and decoding radio signals and transmitting those signals within the assembly) without signal processing capabilities, – a microprocessor capable of receiving remote control messages and controlling the tuner chipset, for use in the manufacture of home entertainment systems ⁽²⁾ | 0 % | p/st | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8529 90 65 | 28 | <p>Electronic assembly comprising at least a printed circuit board with:</p> <ul style="list-style-type: none"> – processors for multi-media applications and video signal processing, – FPGA (Field Programmable Gate Array), – Flash memory, – operating memory, – USB-interface, – with or without HDMI, VGA- and RJ-45 interfaces, – sockets and plugs for connecting a LCD-display, a LED lighting and a control panel | 0 % | p/st | 31.12.2020 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8529 90 65 | 40 | Printed circuit board subassembly, comprising: <ul style="list-style-type: none"> – a radio tuner, capable of receiving and decoding radio signals and transmitting those signals within the assembly, with a signal decoder, – a radio frequency (RF) remote control receiver, – an infrared remote control signal transmitter, – a SCART signal generator, – a TV state sensor, for use in the manufacture of home entertainment systems ⁽²⁾ | 0 % | p/st | 31.12.2019 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8529 90 92 | 52 | <p>LCD module, glass or plastic covered and optically bonded, with</p> <ul style="list-style-type: none"> – a diagonal measurement of the screen of 12 cm or more but not more than 31 cm, – LED backlighting, – a printed circuit board with EEPROM (Electrically Erasable Programmable Read-Only Memory), microcontroller, timing controller and other active and passive components, – a plug for power supply and CAN (Controller Area Network) and LVDS (Low Voltage Differential Signalling) interfaces, – whether or not with electronic components to generate additional control indicators for vehicle information on the display, | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------|-------|---|-------------------------|--------------------|------------------------------------|
| | | <ul style="list-style-type: none"> – with or without a touch screen, – without a signal processing module, – in a housing with additional LED indicators for warning lights, – with or without a gear shift indicator and a photo sensor, of a kind used as a driver information display in motor vehicles of Chapter 87 ⁽²⁾ | | | |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8529 90 92 | 54 | <p>LCD display with:</p> <ul style="list-style-type: none"> – a touch panel, – at least one printed circuit board for simple slave device pixel addressing (Timing Controller function) and touch control, with EEPROM (Electrically Erasable Programmable Read-Only Memory) for display settings, – a diagonal screen measurement of 15 cm or more but not more than 21 cm, – a backlight, – a LVDS (Low Voltage Differential Signalling) and a power supply connector, <p>for use in the manufacture of motor vehicles of Chapter 87⁽²⁾</p> | 0 % | - | 31.12.2023 |
| ex 8529 90 92 | 57 | Metal holder, metal fixing item or internal stiffener of metal, for use in the manufacture of televisions, monitors and video players ⁽²⁾ | 0 % | p/st | 31.12.2021 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8535 90 00 | 30 | Semiconductor module switch in a casing: <ul style="list-style-type: none"> – consisting of an IGBT transistor chip and a diode chip on one or more lead frames, – for a voltage of 600 V or 1 200 V | 0 % | p/st | 31.12.2020 |
| ex 8537 10 91 | 57 | Programmable memory control board with: <ul style="list-style-type: none"> – 4 or more stepper motor drivers, – 4 or more outputs with MOSFET transistors, – a main processor, – 3 or more inputs for temperature sensors, – for a voltage of 10 V or more but not more than 30 V, for use in the manufacture of 3D printers ⁽²⁾ | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8537 10 91 | 59 | Electronic control units for controlling inter axle torque transferring in all-wheel drive vehicles including: <ul style="list-style-type: none"> – a printed circuit board with programmable memory controller, – one single connector, and – working at 12 V | 0 % | - | 31.12.2023 |
| ex 8537 10 91 | 63 | Electronic control units able to control automatic continuous variable transmission for passenger vehicles including: <ul style="list-style-type: none"> – a printed circuit board with programmable memory controller, – a metallic housing, – one single connector, – working at 12 V | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8537 10 91 | 67 | <p>Electronic Engine Control Unit (ECU) with:</p> <ul style="list-style-type: none"> – a printed circuit board (PCB), – 12 Volts voltage, – reprogrammable, – a micro-processor that can control, evaluate and manage support service functions in cars (injection and ignition advance values of fuel, fuel and air flow rate), <p>for use in the manufacture of goods of Chapter 87⁽²⁾</p> | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| ex 8708 40 20 ex 8708 40 50 | 60 50 | Automatic transmission assembly with rotary gear shifter with: <ul style="list-style-type: none"> – aluminium casting housing, – differential gear, – 9 Speed automatic, – electronic range select gear selection system, with dimensions of: <ul style="list-style-type: none"> – a width of 330 mm or more but not more than 420 mm, – a height of 380 mm or more but not more than 450 mm, – a length of 580 mm or more but not more than 690 mm, for use in the manufacture of the vehicles in heading 87 ⁽²⁾ | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|--|----------------------|--|-------------------------|--------------------|------------------------------------|
| ex 8708 50 20 ex 8708 50 99 ex 8708 99 10 ex 8708 99 97 | 60 15 45 65 | Car transfer case with single input, dual output, to distribute torque between front and rear axles in an aluminium housing, with dimension of not more than 565 x 570 x 510 mm, comprising at least: – an actuator, and – a interior distribution by chain | 0 % | - | 31.12.2019 |
| ex 8708 50 20 ex 8708 50 99 | 65 20 | Intermediate steel shaft connecting the gearbox with semi-axle with: – a length of 300 mm or more but not more than 650 mm, – a spline end on both sides, – whether or not with a pressed bearing in the case, – whether or not with a holder, for use in the manufacture of goods of Chapter 87 ⁽²⁾ | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| ex 8708 50 20 ex 8708 50 99 | 70 25 | <p>Housing of tripod type half shaft inboard joint for transmitting a torque from engine and transmission to wheels of motor vehicles with:</p> <ul style="list-style-type: none"> – an outer diameter of 67,0 mm or more but not more than 84,5 mm, – 3 cold calibrated roller tracks with a diameter of 29,90 mm or more but not more than 36,60 mm, – sealing diameter 34,0 mm or more but not more than 41,0 mm, without lead angle, – spline with 21 teeth or more but not more than 35, – bearing seat diameter of 25,0 mm or more but not more than 30,0 mm, with or without oil grooves | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| ex 8708 50 20 ex 8708 50 99 | 75 35 | <p>Outboard joint assembly for transmitting a torque from engine and transmission to wheels of motor vehicles, consisting of:</p> <ul style="list-style-type: none"> – an inner race with 6 ball tracks for running with the bearing balls with a diameter 15,0 mm or more but not more than 20,0 mm, – an outer race with 6 ball tracks for running with 6 bearing balls, made of steel with carbon content of 0,45 % or more but not more than 0,58 %, with thread and with a spline with 26 teeth or more but not more than 38, – a spherical cage keeping bearing balls in the ball tracks of outer race and inner race in proper angular position, made of material suitable for carburizing with carbon content of 0,14 % or more but not more than 0,25 %, and – with a grease compartment, <p>capable of working at constant speed at variable articulation angle not higher than 50 degrees</p> | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8708 80 99 | 20 | <p>Aluminium suspension link arm, with dimensions of:</p> <ul style="list-style-type: none"> – a height of 50 mm or more but not more than 150 mm, – a width of 10 mm or more but not more than 100 mm, – a length of 100 mm or more but not more than 600 mm, – a mass of 1000 g or more but not more than 3000 g, <p>equipped with at least two bushed holes made of aluminium alloy with the following characteristics:</p> <ul style="list-style-type: none"> – a tensile strength of 200 mPa or more, – a strength of 19 kN or more, – a stiffness of 5 kN/mm or more but not more than 9 kN/mm, – a frequency of 400 Hz or more but not more than 600 Hz | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8708 92 99 | 10 | Exhaust system inner liner: <ul style="list-style-type: none"> – with a wall thickness of 0,7 mm or more but not more than 1,3 mm, – made of stainless steel sheets or coil class 1.4310 and 1.4301 according to norm EN 10088, – whether or not with mounting holes, for use in the manufacture of exhaust systems for automobiles ⁽²⁾ | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 8708 92 99 | 20 | Pipe for guiding exhaust gases from the combustion engine: <ul style="list-style-type: none"> – with a diameter of 40 mm or more but not more than 100 mm, – with a length of 90 mm or more but not more than 410 mm, – with a wall thickness of 0,7 mm or more but not more than 1,3 mm, – of stainless steel, for use in the manufacture of exhaust systems for automobiles ⁽²⁾ | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 8708 92 99 | 30 | Exhaust system end cover: <ul style="list-style-type: none"> – with a wall thickness of 0,7 mm or more but not more than 1,3 mm, – made of stainless steel class 1.4310 and 1.4301 according to norm EN 10088, – whether or not with inner liner, – whether or not with surface treatment, for use in the manufacture of exhaust systems for automobiles ⁽²⁾ | 0 % | - | 31.12.2023 |
| ex 9001 90 00 | 55 | Optical, diffuser, reflector or prism sheets, unprinted diffuser plates, whether or not possessing polarising properties, specifically cut | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 9002 11 00 | 15 | <p>Infrared lens with motorised focus adjustment,</p> <ul style="list-style-type: none"> – using wavelengths of 3 µm or more but not more than 5 µm, – providing a clear picture from 50 m to infinity, – with fields of vision sizes of 3° x 2,25° and 9° x 6,75 °, – with a weight of not more than 230 g, – with a length of not more than 88 mm, – with a diameter of not more than 46 mm, – athermalized, <p>for use in the manufacture of thermal imaging cameras, infrared binoculars, weapons scopes⁽²⁾</p> | 0 % | - | 31.12.2020 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 9002 11 00 | 18 | <p>Lens assembly consisting of a cylinder-shaped cover made of metal or plastic and optical elements with:</p> <ul style="list-style-type: none"> – a horizontal field of view range to a maximum of 120 deg, – a diagonal field of view range to a maximum of 92 deg, – a focal length to a maximum of 7,50 mm, – a relative aperture of a maximum of F/2,90, – a maximum diameter of 22 mm, <p>of a kind used for the production of CMOS (Complementary metal–oxide–semiconductor) automotive cameras</p> | 0 % | - | 31.12.2023 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| ex 9002 11 00 | 25 | <p>Infrared optical unit composed of</p> <ul style="list-style-type: none"> – a monocrystalline silicon lens with a diameter of 84 mm ($\pm 0,1$ mm), and – a monocrystalline germanium lens with a diameter of 62 mm ($\pm 0,05$ mm), <p>assembled on a machined aluminium alloy support, of a kind used for thermal imaging cameras</p> | 0 % | - | 31.12.2021 |
| ex 9002 11 00 | 35 | <p>Infrared optical unit composed of</p> <ul style="list-style-type: none"> – a silicon lens with a diameter of 29 mm ($\pm 0,05$ mm), and – a monocrystalline calcium fluoride lens with a diameter of 26 mm ($\pm 0,05$ mm), <p>assembled on a machined aluminium alloy support, of kind a used for thermal imaging cameras</p> | 0 % | - | 31.12.2021 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 9002 11 00 | 45 | Infrared optical unit <ul style="list-style-type: none"> – with a silicon lens of a diameter of 62 mm ($\pm 0,05$ mm), – mounted on a machined aluminium alloy support, of a kind used for thermal cameras | 0 % | - | 31.12.2021 |
| ex 9002 11 00 | 55 | Infrared optical unit composed of <ul style="list-style-type: none"> – a germanium lens with a diameter of 11 mm ($\pm 0,05$ mm), – a monocrystalline calcium fluoride lens with a diameter of 14 mm ($\pm 0,05$ mm), and – a silicon lens with a diameter of 17 mm ($\pm 0,05$ mm), assembled on a machined aluminium alloy support, of a kind used for thermal imaging cameras | 0 % | - | 31.12.2021 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| ex 9002 11 00 | 65 | Infrared optical unit – with a silicon lens with a diameter of 26 mm ($\pm 0,1$ mm), – mounted on a machined aluminium alloy support, of a kind used for thermal imaging cameras | 0 % | - | 31.12.2021 |
| ex 9002 11 00 | 75 | Infrared optical unit composed of – a germanium lens with a diameter of 19 mm ($\pm 0,05$ mm), – a monocrystalline calcium fluoride lens with a diameter of 18 mm ($\pm 0,05$ mm), – a germanium lens with a diameter of 20,6 mm ($\pm 0,05$ mm), assembled on a machined aluminium alloy support, of a kind used for thermal imaging cameras | 0 % | - | 31.12.2021 |

| CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| ex 9029 20 31 ex 9029 90 00 | 20 30 | <p>Clustered instrument panel with the microprocessor control board, with or without stepping motors, and LED indicators showing at least:</p> <ul style="list-style-type: none"> – speed, – engine revolutions, – engine temperature, – the fuel level, <p>communicating via CAN-BUS and/or K-LINE protocols, of a kind used in the manufacture of goods of Chapter 87</p> | 0 % | p/st | 31.12.2019 |

- (2) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)