Council of the European Union

Brussels, 10 November 2026
(OR. en)

15700/26
ADD 1

**Interinstitutional File:**
**2026/0353 (NLE)**

UD 332

**PROPOSAL**

| | |
|---|---|
| From: | Secretary-General of the European Commission, signed by Ms Martine DEPREZ, Director |
| date of receipt: | 10 November 2026 |
| To: | Ms Thérèse BLANCHET, Secretary-General of the Council of the European Union |
| No. Cion doc.: | COM(2026) 613 annex |
| Subject: | ANNEX to the Proposal for a Council Regulation amending Regulation (EU) 2021/2283 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products |

Delegations will find attached document COM(2026) 613 annex.

Encl.: COM(2026) 613 annex

EUROPEAN
COMMISSION

Brussels, 10.11.2026
COM(2026) 613 final

ANNEX

**ANNEX**

**to the**

**Proposal for a Council Regulation**

**amending Regulation (EU) 2021/2283 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products**

# ANNEX

‘ANNEX

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2849 | ex 0710 80 69 | 10 | Mushrooms of the species *Auricularia polytricha* (uncooked or cooked by steaming or boiling), frozen, for the manufacture of prepared meals (1)(2) | 01.01-31.12 | 700 tonnes | 0 % |
| *09.2517 | ex 1517 90 99 | 92 | Microbial oil, refined, used in the manufacture of products other than animal feed:<br>— containing by weight 10 % or more but not more than 80 % of eicosapentaenoic acid, and<br>— with an eicosapentaenoic acid/(eicosapentaenoic acid+docosahexenoic acid) value of 0,2 or more, and<br>— standardised with vegetable oil | 01.01-31.12 | 500 tonnes | 0 % |
| 09.2913 | ex 2401 10 35<br>ex 2401 10 70<br>ex 2401 10 95<br>ex 2401 10 95<br>ex 2401 10 95<br>ex 2401 20 35<br>ex 2401 20 70<br>ex 2401 20 95<br>ex 2401 20 95<br>ex 2401 20 95 | 91<br>10<br>11<br>21<br>91<br>91<br>10<br>11<br>21<br>91 | Natural unmanufactured tobacco, whether or not cut in regular size, having a custom value of not less than EUR 450 per 100 kg net weight, for use as binder or wrapper for the manufacture of goods falling within subheading 2402 10 00 (1) | 01.01-31.12 | 3 000 tonnes | 0 % |
| 09.2828 | 2712 20 90 | | Paraffin wax containing by weight less than 0,75 % of oil | 01.01-31.12 | 180 000 tonnes | 0 % |
| 09.2600 | ex 2712 90 39 | 10 | Slack wax (CAS RN 64742-61-6) | 01.01-31.12 | 100 000 tonnes | 0 % |
| 09.2578 | ex 2811 19 80 | 50 | Sulphamidic acid (CAS RN 5329-14-6) with a purity by weight of 95 % or more, whether or not with not more than 5 % addition of the anti-caking agent silicon dioxide (CAS RN 112926-00-8) | 01.01-31.12 | 27 000 tonnes | 0 % |
| 09.2806 | ex 2825 90 40 | 30 | Tungsten trioxide, including blue tungsten oxide (CAS RN 1314-35-8 or CAS RN 39318-18-8) | 01.01-31.12 | 12 000 tonnes | 0 % |
| 09.2819 | ex 2833 25 00 | 30 | Copper hydroxide sulfate (Cu4(OH)6(SO4)), hydrate (CAS RN 12527-76-3) with a purity by weight of 98 % or more | 01.01-31.12 | 240 000 kilograms | 0 % |
| 09.2872 | ex 2833 29 80 | 40 | Caesium sulphate (CAS RN 10294-54-9) in solid form or as aqueous solution containing by weight 48 % or more but not more than 52 % of caesium sulphate | 01.01-31.12 | 400 tonnes | 0 % |
| 09.2567 | ex 2903 22 00 | 10 | Trichloroethylene (CAS RN 79-01-6) with a purity by weight of 99 % or more | 01.01-31.12 | 11 885 000 kilograms | 0 % |
| 09.2837 | ex 2903 79 30 | 20 | Bromochloromethane (CAS RN 74-97-5) | 01.01-31.12 | 600 tonnes | 0 % |
| 09.2933 | ex 2903 99 80 | 30 | 1,3-Dichlorobenzene (CAS RN 541-73-1) | 01.01-31.12 | 2 600 tonnes | 0 % |
| 09.2700 | ex 2905 12 00 | 10 | Propan-1-ol (propyl alcohol) (CAS RN 71-23-8) | 01.01-31.12 | 15 000 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2830 | ex 2906 19 00 | 40 | Cyclopropylmethanol (CAS RN 2516-33-8) | 01.01-31.12 | 20 tonnes | 0 % |
| 09.2851 | ex 2907 12 00 | 10 | O-cresol (CAS RN 95-48-7) having a purity of not less than 98,5 % by weight | 01.01-31.12 | 20 000 tonnes | 0 % |
| 09.2704 | ex 2909 49 80 | 20 | 2,2,2',2'-Tetrakis(hydroxymethyl)-3,3'-oxydipropan-1-ol (CAS RN 126-58-9) | 01.01-31.12 | 500 tonnes | 0 % |
| 09.2010 | ex 2912 29 00 | 75 | Cyclohex-3-ene-1-carbaldehyde (CAS RN 100-50-5) with a purity by weight of 98 % or more | 01.01-31.12 | 155 000 kilograms | 0 % |
| 09.2565 | ex 2914 19 90 | 70 | Calcium acetylacetonate (CAS RN 19372-44-2) with a purity by weight of 95 % or more | 01.01-31.12 | 400 tonnes | 0 % |
| 09.2852 | ex 2914 29 00 | 60 | Cyclopropyl methyl ketone (CAS RN 765-43-5) | 01.01-31.12 | 300 tonnes | 0 % |
| *09.2638 | ex 2915 21 00 | 10 | Acetic acid (CAS RN 64-19-7) with a purity by weight of 99 % or more | 01.01-31.12 | 500 000 tonnes | 0 % |
| 09.2679 | 2915 32 00 | | Vinyl acetate (CAS RN 108-05-4) | 01.01-31.12 | 370 000 tonnes | 0 % |
| 09.2728 | ex 2915 90 90 | 85 | Ethyl trifluoroacetate (CAS RN 383-63-1) | 01.01-31.12 | 400 tonnes | 0 % |
| 09.2665 | ex 2916 19 95 | 30 | Potassium (E,E)-hexa-2,4-dienoate (CAS RN 24634-61-5) | 01.01-31.12 | 8 250 tonnes | 0 % |
| 09.2684 | ex 2916 39 90 | 28 | 2,5-Dimethylphenylacetyl chloride (CAS RN 55312-97-5) | 01.01-31.12 | 700 tonnes | 0 % |
| 09.2599 | ex 2917 11 00 | 40 | Diethyl oxalate (CAS RN 95-92-1) | 01.01-31.12 | 500 tonnes | 0 % |
| 09.2769 | ex 2917 13 90 | 20 | Dimethyl sebacate (CAS RN 106-79-6) with a purity by weight of 97 % or more | 01.01-31.12 | 1 000 tonnes | 0 % |
| 09.2634 | ex 2917 19 80 | 40 | Dodecanedioic acid (CAS RN 693-23-2), of a purity by weight of more than 98,5 % | 01.01-31.12 | 8 000 tonnes | 0 % |
| 09.2540 | ex 2917 37 00 | 10 | Dimethyl terephthalate (CAS RN 120-61-6) with a purity by weight of 95 % or more | 01.01-31.12 | 57 500 tonnes | 0 % |
| 09.2017 | ex 2918 11 00 | 20 | L-(+)-lactic acid (CAS RN 79-33-4) with a purity by weight of 99 % or more, for use in the manufacturing of:<br>— esters and other derivatives (i.e. products obtained from a chemical reaction with the formation of new intramolecular bonds), or<br>— solutions produced under GMP (Good Manufacturing Practice) conditions to be supplied to the pharmaceutical industry<br>(1) | 01.01-31.12 | 55 000 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2646 | ex 2918 29 00 | 75 | Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (CAS RN 2082-79-3) with:<br>— a sieve passing fraction at a mesh width of 500 µm of more than 99 % by weight, and<br>— a melting point of 49 °C or more, but not more than 54 °C,<br>for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates) (1) | 01.01-31.12 | 380 tonnes | 0 % |
| 09.2647 | ex 2918 29 00 | 80 | Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8) with:<br>— a sieve passing fraction at a mesh width of 250 µm of more than 75 % by weight and at a mesh width of 500 µm of more than 99 % by weight, and<br>— a melting point of 110 °C or more, but not more than 125 °C,<br>for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates) (1) | 01.01-31.12 | 140 tonnes | 0 % |
| 09.2975 | ex 2918 30 00 | 10 | Benzophenone-3,3',4,4'-tetracarboxylic dianhydride (CAS RN 2421-28-5) | 01.01-31.12 | 1 000 tonnes | 0 % |
| 09.2032 | ex 2920 29 00 | 35 | Fosetyl-sodium (ISO)(CAS RN 39148-16-8) in the form of an aqueous solution, containing by weight 39 % or more, but not more than 41 % of fosetyl-sodium | 01.01-31.12 | 521 tonnes | 0 % |
| 09.2598 | ex 2921 19 99 | 75 | Octadecylamine (CAS RN 124-30-1) | 01.01-31.12 | 400 tonnes | 0 % |
| 09.2649 | ex 2921 29 00 | 60 | Bis(2-dimethylaminoethyl)(methyl)amine (CAS RN 3030-47-5) | 01.01-31.12 | 1 700 tonnes | 0 % |
| 09.2617 | ex 2921 42 00 | 89 | 4-Fluoro-N-(1-methylethyl)benzeneamine (CAS RN 70441-63-3) | 01.01-31.12 | 500 tonnes | 0 % |
| 09.2602 | ex 2921 51 19 | 10 | O-phenylenediamine (CAS RN 95-54-5) | 01.01-31.12 | 1 800 tonnes | 0 % |
| 09.2921 | ex 2922 19 00 | 22 | 2-(dimethylamino)ethyl acrylate (CAS RN 2439-35-2) with a purity by weight of 99 % or more | 01.01-31.12 | 14 000 tonnes | 0 % |
| 09.2545 | ex 2922 29 00 | 63 | Aclonifen (ISO) (CAS RN 74070-46-5) with a purity by weight of 97 % or more | 01.01-31.12 | 4 000 tonnes | 0 % |
| *09.2575 | ex 2923 90 00 | 87 | 3-Chloro-2-hydroxypropyl)trimethylammonium chloride (CAS RN 3327-22-8), in the form of an aqueous solution containing by weight 65 % or more but not more than 71 % 3-chloro-2-hydroxypropyl)trimethylammonium chloride | 01.01-31.12 | 4 000 tonnes | 0 % |
| *09.2922 | ex 2923 90 00 | 88 | Aqueous solution containing by weight 78 % or more but not more than 82 % of [2-(acryloyloxy)ethyl]trimethylammonium chloride (CAS RN 44992-01-0) | 01.01-31.12 | 20 000 tonnes | 0 % |
| 09.2854 | ex 2924 19 00 | 85 | 3-Iodoprop-2-yn-1-yl butylcarbamate (CAS RN 55406-53-6) | 01.01-31.12 | 450 tonnes | 0 % |
| 09.2874 | ex 2924 29 70 | 87 | Paracetamol (INN) (CAS RN 103-90-2) | 01.01-31.12 | 20 000 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2550 | ex 2926 90 70 | 31 | Lambda-cyhalothrin (ISO) (CAS RN 91465-08-6) with a purity by weight of 97 % or more | 01.01-31.12 | 2 200 tonnes | 0 % |
| 09.2856 | ex 2926 90 70 | 84 | 2-Nitro-4(trifluoromethyl)benzonitrile (CAS RN 778-94-9) | 01.01-31.12 | 900 tonnes | 0 % |
| 09.2685 | ex 2929 90 90 | 30 | Nitroguanidine (CAS RN 556-88-7) | 01.01-31.12 | 6 500 tonnes | 0 % |
| 09.2597 | ex 2930 90 95 | 94 | Bis[3-(triethoxysilyl)propyl]disulphide (CAS RN 56706-10-6) | 01.01-31.12 | 6 000 tonnes | 0 % |
| 09.2596 | ex 2930 90 95 | 96 | 2-Chloro-4-(methylsulphonyl)-3-((2,2,2-trifluoroethoxy)methyl) benzoic acid (CAS RN 120100-77-8) | 01.01-31.12 | 300 tonnes | 0 % |
| 09.2580 | ex 2931 90 00 | 75 | Hexadecyltrimethoxysilane (CAS RN 16415-12-6) with a purity by weight of at least 95 %, for use in the manufacture of polyethylene [(1)] | 01.01-31.12 | 165 tonnes | 0 % |
| 09.2696 | ex 2932 20 90 | 25 | Decan-5-olide (CAS RN 705-86-2) | 01.01-31.12 | 6 000 kilograms | 0 % |
| 09.2697 | ex 2932 20 90 | 30 | Dodecan-5-olide (CAS RN 713-95-1) | 01.01-31.12 | 6 000 kilograms | 0 % |
| 09.2812 | ex 2932 20 90 | 77 | Hexan-6-olide (CAS RN 502-44-3) | 01.01-31.12 | 4 000 tonnes | 0 % |
| 09.2541 | ex 2933 19 90 | 73 | 2,4-Dihydro-2,5-dimethyl-3H-pyrazol-3-one (CAS RN 2749-59-9) with a purity by weight of 99 % or more | 01.01-31.12 | 150 tonnes | 0 % |
| 09.2839 | ex 2933 39 99 | 09 | 2-(2-Pyridyl)ethanol (CAS RN 103-74-2) with a purity by weight of 99 % or more | 01.01-31.12 | 700 tonnes | 0 % |
| 09.2543 | ex 2933 39 99 | 13 | Imazamox (ISO) (CAS RN 114311-32-9) with a purity by weight of 95 % or more | 01.01-31.12 | 300 tonnes | 0 % |
| 09.2546 | ex 2933 39 99 | 46 | Fluopicolide (ISO) (CAS RN 239110-15-7) with a content by weight of 97 % or more | 01.01-31.12 | 250 tonnes | 0 % |
| *09.2516 | ex 2933 39 99 | 95 | Fluopyram (ISO) (CAS RN 658066-35-4) with a purity by weight of 96,5 % or more | 01.01-31.12 | 150 tonnes | 0 % |
| 09.2025 | ex 2933 59 95 | 82 | Ametoctradin (ISO) (CAS RN 865318-97-4) with a purity by weight of 98 % or more | 01.01-31.12 | 353 500 kilograms | 0 % |
| 09.2547 | ex 2933 69 80 | 13 | Metribuzin (ISO) (CAS RN 21087-64-9) with a purity by weight of 93 % or more | 01.01-31.12 | 225 tonnes | 0 % |
| 09.2860 | ex 2933 69 80 | 30 | 1,3,5-Tris[3-(dimethylamino)propyl]hexahydro-1,3,5-triazine (CAS RN 15875-13-5) | 01.01-31.12 | 600 tonnes | 0 % |
| 09.2566 | ex 2933 99 80 | 05 | 1,4,7,10-Tetraazacyclododecane (CAS RN 294-90-6) with a purity by weight of 96 % or more | 01.01-31.12 | 60 tonnes | 0 % |
| 09.2544 | ex 2933 99 80 | 23 | Tebuconazole (ISO) (CAS RN 107534-96-3) with a purity by weight of 95 % or more | 01.01-31.12 | 150 tonnes | 0 % |
| 09.2658 | ex 2933 99 80 | 73 | 5-(Acetoacetylamino)benzimidazolone (CAS RN 26576-46-5) | 01.01-31.12 | 400 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2549 | ex 2934 99 90 | 16 | Difenoconazole (ISO) (CAS RN 119446-68-3) | 01.01-31.12 | 1 000 tonnes | 0 % |
| 09.2548 | ex 2934 99 90 | 24 | Flufenacet (ISO) (CAS RN 142459-58-3) with a purity by weight of 95 % or more | 01.01-31.12 | 900 tonnes | 0 % |
| 09.2593 | ex 2934 99 90 | 67 | 5-Chlorothiophene-2-carboxylic acid (CAS RN 24065-33-6) | 01.01-31.12 | 45 000 kilograms | 0 % |
| 09.2675 | ex 2935 90 90 | 79 | 4-[[(2-Methoxybenzoyl)amino]sulfonyl]benzoyl chloride (CAS RN 816431-72-8) | 01.01-31.12 | 1 000 tonnes | 0 % |
| 09.2945 | ex 2940 00 00 | 20 | D-Xylose (CAS RN 58-86-6) | 01.01-31.12 | 400 tonnes | 0 % |
| 09.2659 | ex 3802 90 00 | 19 | Soda flux calcinated diatomaceous earth | 01.01-31.12 | 35 000 tonnes | 0 % |
| 09.2908 | ex 3804 00 00 | 10 | Sodium lignosulphonate (CAS RN 8061-51-6) | 01.01-31.12 | 40 000 tonnes | 0 % |
| 09.2889 | 3805 10 90 | | Sulphate turpentine | 01.01-31.12 | 25 000 tonnes | 0 % |
| 09.2935 | ex 3806 10 00 | 10 | Rosin and resin acids obtained from fresh oleoresins | 01.01-31.12 | 280 000 tonnes | 0 % |
| 09.2923 | ex 3808 94 20 | 40 | Aqueous solution containing by weight:<br>— 10,0 % or more but not more than 11,3 % of 5-chloro-2-methyl-2H-isothiazol-3-one,<br>— 3,0 % or more but not more than 4,1 % of 2-methyl-2H-isothiazol-3-one,<br>— a combined concentration of isothiazolones (CAS RN 55965-84-9) of 13,0 % or more but not more than 15,4 %,<br>— 18 % or more but not more than 22 % of nitrates, calculated as sodium nitrate, and<br>— 5 % or more but not more than 8 % of chlorides, calculated as sodium chloride | 01.01-31.12 | 3 000 tonnes | 0 % |
| 09.2876 | ex 3811 29 00 | 57 | Additives consisting of reaction products of diphenylamine and branched nonenes with:<br>— more than 20 % but not more than 50 % by weight 4-monononyldiphenylamine, and<br>— more than 50 % but not more than 80 % by weight 4,4'-dinonyldiphenylamine,<br>— a total percentage of 2,4-dinonyldiphenylamine and 2,4'-dinonyldiphenylamine of not more than 15 % by weight,<br>used for the manufacture of lubricating oils (1) | 01.01-31.12 | 900 tonnes | 0 % |
| 09.2033 | ex 3811 29 00 | 79 | Additives, consisting of the reaction products of 1,3,4-thiadiazolidine-2,5-dithione with hydrogen peroxide and tert-nonanethiol, containing by weight:<br>— 70 % or more of 2,5-bis(tert-nonyldithio)-[1,3,4]-thiadiazole (CAS RN 89347-09-1), and<br>— 10 % or more of 5-(tert-nonyldithio)- 1,3,4-thiadiazole-2(3H)-thione (CAS RN 97503-12-3),<br>for use in the manufacture of blends of additives for lubricating oils (1) | 01.01-31.12 | 500 tonnes | 0 % |
| 09.2027 | ex 3815 19 90 | 82 | Catalyst consisting of organo-metallic compounds of boron, titanium and aluminium, fixed on a support of silicon dioxide, in the form of powder | 01.01-31.12 | 15 600 kilograms | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2814 | ex 3815 90 90 | 76 | Catalyst consisting of titanium dioxide and tungsten trioxide | 01.01-31.12 | 3 000 tonnes | 0 % |
| *09.2542 | ex 3824 99 92 | 97 | Mixture containing bis[3-(triethoxysilyl)propyl]polysulfides (CAS RN 211519-85-6) with a purity by weight of 84 % or more | 01.01-31.12 | 5 000 tonnes | 0 % |
| 09.2907 | ex 3824 99 93 | 67 | Mixture of phytosterols, in the form of powder, containing by weight:<br>— 75 % or more of sterols,<br>— not more than 25 % of stanols,<br>for use in the manufacture of stanols/sterols or stanol/sterol esters (1) | 01.01-31.12 | 2 500 tonnes | 0 % |
| 09.2568 | ex 3824 99 96 | 91 | Mixture, in pellet form, containing by weight:<br>— 49 % or more but not more than 50 % of bis[3-(triethoxysilyl)propyl] polysulphides (CAS RN 211519-85-6), and<br>— 50 % or more but not more than 51 % of carbon black (CAS RN 1333-86-4),<br>of which 75 % by weight or more pass through a sieve with an aperture of 0,60 mm, but not more than 10 % pass through a sieve with an aperture of 0,25 mm (as determined by the ASTM D1511 method) | 01.01-31.12 | 2 100 tonnes | 0 % |
| 09.2820 | ex 3827 90 00 | 10 | Mixtures containing by weight:<br>— 60 % or more but not more than 90 % of 2-chloropropene (CAS RN 557-98-2),<br>— 8 % or more but not more than 14 % of (Z)-1-chloropropene (CAS RN 16136-84-8),<br>— 5 % or more but not more than 23 % of 2-chloropropane (CAS RN 75-29-6),<br>— not more than 6 % of 3-chloropropene (CAS RN 107-05-1), and<br>— not more than 1 % of ethyl chloride (CAS RN 75-00-3) | 01.01-31.12 | 6 000 tonnes | 0 % |
| 09.2671 | ex 3905 99 90 | 81 | Poly(vinyl butyral)(CAS RN 63148-65-2):<br>— containing by weight 17,5 % or more, but not more than 20 % of hydroxyl groups, and<br>— with a median particle size (D50) of more than 0,6 mm | 01.01-31.12 | 12 500 tonnes | 0 % |
| 09.2846 | ex 3907 40 00 | 25 | Polymer blend of polycarbonate and poly(methyl methacrylate) with a polycarbonate content of not less than 98,5 % by weight, in the form of pellets or granules, with a luminous transmittance of not less than 88,5 %, measured using a test sample with a thickness of 4 mm at a wavelength of $\lambda = 400$ nm (according to ISO 13468-2) | 01.01-31.12 | 2 000 tonnes | 0 % |
| *09.2585 | ex 3907 61 90<br>ex 3907 69 90<br>ex 3907 99 80 | 20<br>20<br>70 | Copolymer of poly(ethylene terephthalate) and cyclohexane dimethanol, containing more than 10 % by weight of cyclohexane dimethanol | 01.01-31.12 | 60 000 tonnes | 2 % |
| 09.2855 | ex 3910 00 00 | 10 | Liquid poly(methylhydrosiloxane) with terminal trimethylsilyl groups (CAS RN 63148-57-2) with a purity by weight of 99,9 % or more | 01.01-31.12 | 1 000 tonnes | 0 % |
| 09.2816 | ex 3912 11 00 | 20 | Cellulose acetate flakes | 01.01-31.12 | 75 000 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| *09.2520 | ex 3912 20 19 | 20 | Nitrocellulose (CAS RN 9004-70-0):<br>— damped or wetted with an alcohol,<br>— with a nitrocellulose content by weight of 60 % or more,<br>— with a nitrogen content by weight of less than 12.3 %;<br>— whether or not containing by weight not more than 2 % additives of a kind used as stabilising agents | 01.01-31.12 | 3 000 000 kilograms | 0 % |
| *09.2521 | ex 3912 20 90 | 20 | Nitrocellulose (CAS RN 9004-70-0):<br>— plasticised with acetyl tributyl citrate (CAS RN 77-90-7),<br>— with a nitrocellulose content by weight of 70 % or more;<br>— whether or not containing by weight not more than 2 % additives of a kind used as stabilising agents | 01.01-31.12 | 400 000 kilograms | 0 % |
| 09.2561 | ex 3912 39 85 | 60 | Hypromellose (INN) (CAS RN 9004-65-3), for use in the manufacturing of food supplements or pharmaceuticals [(1)] | 01.01-31.12 | 2 750 tonnes | 0 % |
| 09.2573 | ex 3913 10 00 | 20 | Sodium alginate extracted from brown seaweed (CAS RN 9005-38-3), with<br>— a loss on drying of not more than 15 % by weight (4h at 105 °C),<br>— a water-insoluble fraction of not more than 2 % by weight, calculated on the dry weight | 01.01-31.12 | 2 000 tonnes | 0 % |
| 09.2641 | ex 3913 90 00 | 87 | Sodium hyaluronate, non sterile, with:<br>— a weight average molecular weight ($M_w$) of not more than 900 000,<br>— an endotoxin level of not more than 0,008 Endotoxin units (EU)/mg,<br>— an ethanol content of not more than 1 % by weight,<br>— an isopropanol content of not more than 0,5 % by weight | 01.01-31.12 | 300 kilograms | 0 % |
| 09.2661 | ex 3920 51 00 | 50 | Sheets of polymethylmethacrylate conforming to standards:<br>— EN 4364 (MIL-P-5425E) and DTD5592A, or<br>— EN 4365 (MIL-P-8184) and DTD5592A | 01.01-31.12 | 100 tonnes | 0 % |
| 09.2645 | ex 3921 14 00 | 20 | Cellular block of regenerated cellulose, impregnated with water containing magnesium chloride and quaternary ammonium compounds, measuring 100 cm (± 10 cm) x 100 cm (± 10 cm) x 40 cm (± 5 cm) | 01.01-31.12 | 1 700 tonnes | 0 % |
| *09.2572 | ex 5205 26 00<br>ex 5205 27 00 | 20<br>20 | Raw white single cotton yarn<br>— of combed fibres,<br>— with a fiber length of 31.75 mm or more UHML (raw material basis according to HVI standard: ASTM D5867), produced from raw cotton with an average UHML of 31.75 mm (measured on the fiber bundle using HVI according to standard ASTM D5867),<br>— produced through the compact ring spinning process with pneumatic compression,<br>— with a minimum tensile strength of 22 cN/tex (yarn testing in accordance with EN ISO 2062, at a test speed of 5.000 mm/min) | 01.01-31.12 | 15 000 tonnes | 0 % |
| 09.2848 | ex 5505 10 10 | 10 | Waste of synthetic fibres (including noils, yarn waste, and garnetted stock) of nylon or other polyamides (PA6 and PA66) | 01.01-31.12 | 10 000 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2721 | ex 5906 99 90 | 20 | Woven and laminated rubberised textile fabric with the following characteristics:<br>— with three layers,<br>— one outer layer consists of acrylic fabric,<br>— the other outer layer consists of polyester fabric,<br>— the middle layer consists of chlorobutyl rubber,<br>— the middle layer has a weight of 452 g/m$^2$ or more but not more than 569 g/m$^2$,<br>— the textile fabric has a total weight of 952 g/m$^2$ or more but not more than 1159 g/m$^2$, and<br>— the textile fabric has a total thickness of 0,8 mm or more but not more than 4 mm,<br>used for the manufacture of the retractable roof of motor vehicles (1) | 01.01-31.12 | 375 000 square meters | 0 % |
| 09.2628 | ex 7019 66 00 | 10 | Glass web woven from glass fibre coated in plastic, of a weight of 120 g/m$^2$(± 10 g/m$^2$), of a type used in rolling insect screens with fixed frames | 01.01-31.12 | 3 000 000 square meters | 0 % |
| *09.2652 | ex 7410 11 00 | 60 | Electrodeposited copper foils with a thickness of 0.018mm, 0.035mm, 0.070mm, 0.105mm, 0.140mm, 0.150mm for copper-clad laminates or printed circuit boards. Supplied in roll or sheet format, in widths from 300 mm to 1,320 mm. | 01.01-31.12 | 1 020 tonnes | 0 % |
| 09.2662 | ex 7410 21 00 | 55 | Plates:<br>— consisting of at least one layer of fibreglass fabric impregnated with epoxide resin,<br>— covered on one or both sides with copper foil with a thickness of not more than 0,15 mm,<br>— with a dielectric constant (DK) of less than 5,4 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2,<br>— with a loss tangent of less than 0,035 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2,<br>— with a comparative tracking index (CTI) of 600 or more | 01.01-31.12 | 108 000 square meters | 0 % |
| 09.2722 | 8104 11 00 | | Unwrought magnesium, containing at least 99,8 % by weight of magnesium | 01.01-31.12 | 120 000 tonnes | 0 % |
| 09.2840 | ex 8104 30 00 | 20 | Magnesium powder:<br>— of purity by weight of 98 % or more, but not more than 99,5 %, and<br>— with a particle size of 0,2 mm or more but not more than 0,8 mm | 01.01-31.12 | 2 000 tonnes | 0 % |
| 09.2629 | ex 8302 49 00 | 91 | Aluminium telescopic handle for use in the manufacture of luggage (1) | 01.01-31.12 | 1 500 000 pieces | 0 % |
| *09.2522 | ex 8409 91 00 | 48 | Fuel pump lobe for press-fit mounting on a crankshaft in a four cylinder engine, made of steel with:<br>— a precision-machined inner bore for interference fit assembly,<br>— a defined outer cam profile for actuating the fuel pump,<br>— cam profile tolerance of 0,05mm,<br>— a length of 25 mm or more but not more than 30 mm,<br>— a width of 50 mm or more but not more than 60 mm, and<br>— a height of 59 mm or more but not more than 71 mm,<br>— a hardness of 58 HRC or more | 01.01-31.12 | 400 000 pieces | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2029 | ex 8409 91 00 | 63 | Cylinder head blank for a four cylinder engine with 10 cores, made of aluminium alloy EN AC-45500, with:<br>— no other components,<br>— a hardness of 90HB or more,<br>— casting defects size of not more than 0,4 mm and not more than 10 defects per $cm^2$,<br>— a dendrite arm space in combustion chamber of not more than 25 µm,<br>— a double deck water jacket design,<br>— a weight of 14 kg or more, but not more than 19 kg,<br>— a length of 460 mm or more, but not more than 510 mm,<br>— a height of 260 mm or more, but not more than 286 mm and<br>— a width of 140 mm or more, but not more than 150 mm | 01.01-31.12 | 200 000 pieces | 0 % |
| *09.2035 | ex 8409 91 00 | 78 | Connecting rod for connecting pistons to the crankshaft of a passenger car engine:<br>— made of an alloy containing 96 % steel and the remainder being vanadium, chromium, nickel, copper, phosphorus, silicon, sulphur, manganese, whether or not titanium, whether or not aluminium,<br>— with two connecting rod bolts,<br>— with a bushing,<br>— of a length of 120 mm or more but not more than 160 mm,<br>— with a surface roughness corresponding to ISO 4287-1997,<br>for use in the manufacture of spark ignition motor vehicle engines (1) | 01.01-31.12 | 570 000 pieces | 0 % |
| 09.2031 | ex 8411 99 00 | 45 | Turbine ring segments, guide and rotor blades as parts of a stationary gas turbine for power generation or as a mechanical drive<br>— made of nickel-based superalloys,<br>— for an operating temperature of more than 600 K but not more than 1600 K,<br>— with a length of not more than 500 mm,<br>— with a width of not more than 900 mm,<br>— with a height of not more than 1300 mm | 01.01-31.12 | 615 tonnes | 0 % |
| 09.2720 | ex 8413 91 00 | 50 | Pump head for two cylinder high pressure pump made of forged steel, with:<br>— milled threaded fittings with a diameter of 10 mm or more but not more than 36,8 mm, and<br>— drilled fuel channels with a diameter of 3,5 mm or more but not more than 10 mm,<br>of a kind used in diesel injection systems | 01.01-31.12 | 65 000 pieces | 0 % |
| 09.2569 | ex 8414 90 00 | 80 | Turbocharger wheel housing of cast aluminium alloy or cast iron:<br>— with a heat resistance up to 400°C,<br>— with a hole of 30 mm or more but not more than 300 mm for the insertion of the compressor wheel,<br>for use in the automotive industry (1) | 01.01-31.12 | 4 000 000 pieces | 0 % |
| 09.2570 | ex 8482 91 90 | 10 | Rollers with a logarithmic profile and a diameter of 25 mm or more but not more than 70 mm or balls with a diameter of 30 mm but not more than 100 mm,<br>— made of 100Cr6 steel or 100CrMnSi6-4 steel (ISO 3290),<br>— with a deviation of 0,5 mm or less as determined with the FBHmethod<br>for use in wind turbine industry (1) | 01.01-31.12 | 600 000 pieces | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2562 | ex 8482 99 00 | 30 | Brass cages with the following characteristics:<br>— continuously or centrifugally cast,<br>— turned,<br>— containing by weight 35 % or more, but not more than 38 % of zinc,<br>— containing by weight 0,75 % or more, but not more than 1,25 % of lead,<br>— containing by weight 1,0 % or more, but not more than 1,4 % of aluminium, and<br>— with a tensile strength of 415 Pa or more,<br>of a kind used for the manufacture of ball bearings | 01.01-31.12 | 550 000 pieces | 0 % |
| *09.2557 | ex 8482 99 00 | 60 | Inner or outer rings made of steel, not hardened or not grinded, outer ring with internal raceway(s), inner ring with external raceway(s), with external diameters of:<br>— 14 mm or more but not more than 77 mm for the inner ring,<br>— 26 mm or more but not more than 101 mm for the outer ring,<br>for use in the manufacture of bearings (1) | 01.01-31.12 | 200 000 000 pieces | 0 % |
| 09.2552 | ex 8482 99 00 | 70 | Male and female parts of cages,<br>— made of flat-rolled steel,<br>— with a diameter of 14,5 mm or more but not more than 420 mm,<br>— the male part including rivets,<br>— the female part including holes,<br>used for manufacturing of deep grove ball bearings (1) | 01.01-31.12 | 1 221 tonnes | 0 % |
| 09.2553 | ex 8482 99 00 | 80 | Punched cages of various diameters,<br>— made of flat rolled steel,<br>— with tensile strength of 270 MPa or more,<br>for the production of tapered roller bearings (1) | 01.01-31.12 | 8 000 000 pieces | 0 % |
| *09.2523 | ex 8483 50 80 | 70 | Decoupler with a rotating inertia with an integrated spring-loaded clutch and damper, used between the engine and the drivetrain system to reduce the transfer of rotational irregularities:<br>— made of non-cast hardened alloy steel (DD13 or 16MnCr5)<br>— a weight of 2,5 kg or more but not more than 13,9 kg,<br>— an outer diameter of 204 mm or more but not more than 350 mm<br>— a thickness of 25 mm or more but not more than 60 mm | 01.01-31.12 | 400 000 pieces | 0 % |
| 09.2560 | ex 8501 31 00 | 85 | Power transmission device for controlling the output of exhaust gas turbochargers, consisting of:<br>— a DC motor of an output not exceeding 600 W,<br>— for usage with a supply voltage of 8 V or more but no more than 48 V,<br>— with motor connection (plug-in connection),<br>— whether or not with position sensor,<br>— whether or not with integrated control and power electronics,<br>— whether or not with spring mechanism for resetting the lever,<br>— built in a housing with reduction gear and lever attached to the motor drive shaft, or<br>— built in a housing with threads integrated into the rotor of the motor for linear movement of the integrated control rod | 01.01-31.12 | 650 000 pieces | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2559 | ex 8501 40 20<br>ex 8501 40 80 | 70<br>70 | Electric AC motor, single-phase, whether or not with commutator<br>— with a nominal output of 180 W or more,<br>— with an input power of 150 W or more but not more than 2 700 W,<br>— with an external diameter of more than 44,8 but not more than 135,2 mm,<br>— with a rated speed of more than 10 000 rpm but not more than 50 000 rpm,<br>— whether or not equipped with air-inducting ventilator,<br>— whether or not with mechanical device (pinion, screws, gear connection etc.) on the shaft,<br>for use in the manufacture of domestic appliances<br>(1) | 01.01-31.12 | 2 000 000 pieces | 0 % |
| *09.2554 | ex 8505 11 20<br>ex 8505 11 30<br>ex 8505 11 80<br>ex 8505 19 90 | 74<br>74<br>74<br>74 | Articles in shape of flat bars, arched bars, quarter sleeves or trapezoid whether or not arched, rounded corners or oblique sides made of ferrite, or cobalt, or samarium or other rare-earth metals, or their alloy,<br>— whether or not overmolded with polymers,<br>— whether or not coated or passivated with a surface treatment,<br>with:<br>— a length of 5 mm or more, but not more than 60 mm,<br>— a width of 5 mm or more, but not more than 40 mm,<br>— a thickness of 3 mm or more, but not more than 15 mm,<br>intended to become permanent magnets after magnetisation | 01.01-31.12 | 460 tonnes | 0 % |
| *09.2555 | ex 8505 11 20<br>ex 8505 11 30<br>ex 8505 11 80 | 76<br>76<br>76 | Articles of an alloy of neodymium, or an alloy of samarium,<br>— whether or not coated or passivated with a surface treatment,<br>— whether or not covered with zinc,<br>— in the shape of rectangles,<br>with:<br>— a length of 13,8 mm or more but not more than 45,2 mm,<br>— a width of 7,8 mm or more but not more than 25,2 mm,<br>— a height of 1,3 mm or more but not more than 4,7 mm,<br>intended to become permanent magnets after magnetisation | 01.01-31.12 | 350 tonnes | 0 % |
| *09.2556 | ex 8505 11 20 | 77 | Article of an alloy of neodymium, in the form of arched rectangles, whether or not coated or passivated with a surface treatment, with:<br>— a width of 9,1 mm or more but not more than 10,5 mm,<br>— a length of 20 mm or more but not more than 30,1 mm,<br>intended to become permanent magnets after magnetization | 01.01-31.12 | 50 tonnes | 0 % |
| 09.2574 | ex 8537 10 91 | 73 | Multifunctional device (instrument cluster) with:<br>— curved TFT LCD display (radius 750 mm) with touch-sensitive surfaces,<br>— microprocessors and memory chips,<br>— acoustic module and loudspeaker,<br>— connections for CAN, 3 x LIN bus, LVDS and Ethernet,<br>— for operating various functions (e.g. chassis, lighting) and<br>— for situation-related display of vehicle and navigation data (e.g. speed, odometer, charge level of the drive battery),<br>for use in the manufacture of passenger cars powered solely by an electric motor covered by HS subheading 8703 80<br>(1) | 01.01-31.12 | 66 900 pieces | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty (%) |
|---|---|---|---|---|---|---|
| 09.2558 | ex 8543 70 90 | 87 | An electronic sound generator, creating an analog signal for a device producing the sound of an engine, containing:<br>— a printed circuit board with a microprocessor and a sound amplifier,<br>— a connector,<br>— a plastic housing,<br>— with or without a metal holder,<br>for use in the manufacture of goods of Chapter 87 (1) | 01.01-31.12 | 30 000 pieces | 0 % |
| *09.2518 | ex 8544 30 00 | 63 | Electrical wiring harness or cable for motor vehicle rear-view system (according to IATF 16949):<br>— with a rated voltage of 12 V or 24 V,<br>— fitted with connectors on both ends,<br>for the manufacture of rear-view systems for motor vehicles (1) | 01.01-31.12 | 7 050 000 pieces | 0 % |
| *09.2519 | ex 8544 30 00 | 78 | Wiring harness to connect the integrated battery system with the car's control systems, containing:<br>— an input connector, whether or not waterproof,<br>— four or more output connectors,<br>— two or more plastic clips for attachment<br>for use in the production of rechargeable batteries for hybrid and electric vehicles (1) | 01.01-31.12 | 100 000 pieces | 0 % |
| 09.2910 | ex 8708 99 97 | 75 | Aluminium alloy support bracket, with mounting holes, whether or not with fixation nuts, for indirect connection of the gearbox to the car body for use in the manufacture of goods of Chapter 87 (1) | 01.01-31.12 | 200 000 pieces | 0 % |
| 09.2668 | ex 8714 91 10<br>ex 8714 91 10<br>ex 8714 91 10 | 21<br>31<br>75 | Bicycle frame, constructed from carbon fibres and artificial resin, for use in the manufacture of bicycles (including electric bicycles) (1) | 01.01-31.12 | 600 000 pieces | 0 % |
| 09.2564 | ex 8714 91 10<br>ex 8714 91 10<br>ex 8714 91 10 | 25<br>35<br>77 | Frame, constructed from aluminium or aluminium and carbon fibres and artificial resin, for the use in the manufacture of bicycles (including electric bicycles) (1) | 01.01-31.12 | 9 600 000 pieces | 0 % |
| 09.2034 | ex 9029 20 31<br>ex 9029 90 00 | 50<br>50 | Clustered instrument panel, communicating via CAN-BUS and/or K-LINE protocols, with:<br>— or without stepping motors,<br>— analogue or digital pointers and dials,<br>— or without microprocessor control board,<br>— or without LED indicators or LCD display,<br>showing at least:<br>— speed,<br>— engine revolutions,<br>— engine temperature,<br>— fuel level,<br>for use in the manufacture of goods of Chapter 87 (1) | 01.01-31.12 | 160 000 pieces | 0 % |

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.'

(2) However, the suspension of tariff duties does not apply where the processing is carried out by retail or catering undertakings.

* New or amendment request.'.