

Brussels, 28 April 2026
(OR. en)

8660/26
ADD 1

**Interinstitutional File:
2026/0095 (NLE)**

UD 113

PROPOSAL

From: Secretary-General of the European Commission, signed by Ms Martine DEPREZ, Director

date of receipt: 27 April 2026

To: Ms Thérèse BLANCHET, Secretary-General of the Council of the European Union

No. Cion doc.: COM(2026) 176 annex

Subject: ANNEX to the Proposal for a COUNCIL REGULATION amending Regulation (EU) 2021/2278 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 of the European Parliament and of the Council on certain agricultural and industrial products

Delegations will find attached document COM(2026) 176 annex.

Encl.: COM(2026) 176 annex



Brussels, 27.4.2026
COM(2026) 176 final

ANNEX

ANNEX

to the

Proposal for a COUNCIL REGULATION

amending Regulation (EU) 2021/2278 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 of the European Parliament and of the Council on certain agricultural and industrial products

ANNEX

The Annex is amended as follows:

- (1) the entries with the following serial numbers are deleted: 0.3341, 0.8865, 0.7594, 0.8425, 0.5110, 0.8425, 0.7540, 0.7541, 0.5495, 0.6802, 0.8795, 0.8877, 0.5987, 0.7056, 0.7056, 0.8668, 0.8669, 0.8680, 0.8675, 0.8647;
- (2) the following entries replace those entries that have the same serial numbers:

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|--|
| 0.4080 | ex 1517 90 99 | 30 | Microbial oil, refined, containing by weight: — 25 % or more but not more than 70 % arachidonic acid and no more than 5 % docosahexenoic acid — standardised with vegetable oil | 0 % | - | 31.12.2026 |
| 0.6144 | ex 2835 10 00 | 50 | Sodium hypophosphite (CAS RN 7681-53-0) with a purity by weight of 97 % or more or as aqueous solution containing by weight 55 % or more but not more than 65 % of sodium hypophosphite | 0 % | - | 31.12.2029 |
| 0.6482 | ex 2841 70 00 | 50 | Hexaammonium heptamolybdate, anhydrous (CAS RN 12027-67-7) or as tetrahydrate (CAS RN 12054-85-2) with a purity by weight of 98 % or more | 0 % | - | 31.12.2029 |
| 0.5936 | ex 2841 90 70 | 20 | Potassium titanium oxide (CAS RN 12056-51-8) in powder form with a purity of 99 % or more | 0 % | - | 31.12.2029 |
| 0.7097 | ex 2842 10 00 | 60 | Aluminosilicate (CAS RN 1318-02-1) with — a purity by weight of 94 % or more, — a zeolite structure of aluminophosphate-eighteen (AEI), and — a phase purity of 90 % or more for use in the manufacture of copper zeolite or washcoat used in the automotive catalyst production ⁽¹⁾ | 0 % | - | 31.12.2026 |
| 0.4529 | ex 2903 99 80 | 28 | Fluorobenzene (CAS RN 462-06-6) with a purity by weight of 99 % or more | 0 % | - | 31.12.2029 |
| 0.6560 | ex 2904 99 00 | 78 | 1-Chloro-2-nitrobenzene (CAS RN 88-73-3) with a purity by weight of 99 % or more | 0 % | - | 31.12.2029 |
| 0.6257 | ex 2906 19 00 | 80 | 4- <i>tert</i> -Butylcyclohexanol (CAS RN 98-52-2) with a purity by weight of 97 % or more | 0 % | - | 31.12.2029 |
| 0.5503 | ex 2909 30 39 | 20 | 1,1'-Propane-2,2-diylbis[3,5-dibromo-4-(2,3-dibromopropoxy)benzene] (CAS RN 21850-44-2) | 0 % | - | 31.12.2026 |
| 0.6649 | ex 2909 30 39 | 30 | 1,1'-(1-Methylethylidene)bis[3,5-dibromo-4-(2,3-dibromo-2-methylpropoxy)]-benzene (CAS RN 97416-84-7) | 0 % | - | 31.12.2030 |
| 0.7828 | ex 2909 30 39 | 50 | 2-(1-Adamantyl)-4-Bromoanisole (CAS RN 104224-63-7) with a purity by weight of 99 % or more | 0 % | - | 31.12.2029 |
| 0.4274 | ex 2914 19 90 | 80 | 3-Methylbutanone (CAS RN 563-80-4) with a purity by weight of 97 % or more | 0 % | - | 31.12.2027 |
| 0.4227 | ex 2914 39 00 | 35 | Benzophenone (CAS RN 119-61-9) with a purity by weight of 99 % or more | 0 % | - | 31.12.2027 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|--|
| 0.7407 | ex 2915 90 90 | 20 | Methyl (R)-2-fluoropropionate (CAS RN 146805-74-5) | 0 % | - | 31.12.2027 |
| 0.7542 | ex 2915 90 90 | 25 | Methyl octanoate (CAS RN 111-11-5), methyl decanoate (CAS RN 110-42-9) or methyl myristate (CAS RN 124-10-7) | 0 % | - | 31.12.2029 |
| 0.6003 | ex 2915 90 90 | 27 | Triethyl orthoformate (CAS RN 122-51-0) with a purity by weight of 99 % or more | 0 % | - | 31.12.2029 |
| 0.5767 | ex 2915 90 90 | 30 | 3,3-Dimethylbutyryl chloride (CAS RN 7065-46-5) | 0 % | - | 31.12.2027 |
| 0.8154 | ex 2915 90 90 | 33 | Ethyl 8-bromooctanoate (CAS RN 29823-21-0) with a purity by weight of 98 % or more | 0 % | - | 31.12.2026 |
| 0.8423 | ex 2915 90 90 | 43 | Trifluoroacetic anhydride (CAS RN 407-25-0) with a purity by weight of 98 % or more | 0 % | - | 31.12.2027 |
| 0.6255 | ex 2915 90 90 | 45 | Trimethyl orthoformate (CAS RN 149-73-5) | 0 % | - | 31.12.2029 |
| 0.8457 | ex 2915 90 90 | 53 | 3-Chloro-2,2-dimethylpropanoyl chloride (CAS RN 4300-97-4) with a purity by weight of 98 % or more | 0 % | - | 31.12.2027 |
| 0.4954 | ex 2915 90 90 | 60 | Ethyl-6,8-dichlorooctanoate (CAS RN 1070-64-0) | 0 % | - | 31.12.2030 |
| 0.3638 | ex 2918 29 00 | 85 | Hexamethylene bis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate] (CAS RN 35074-77-2) with a purity by weight of 97 % or more | 0 % | - | 31.12.2029 |
| 0.3978 | ex 2921 42 00 | 38 | 2-Nitroaniline (CAS RN 88-74-4) with a purity by weight of 99 % or more | 0 % | - | 31.12.2029 |
| 0.2609 | ex 2921 45 00 | 15 | <i>N</i> -1-Naphthylaniline (CAS RN 90-30-2) with a purity by weight of 98 % or more | 0 % | - | 31.12.2029 |
| 0.4160 | ex 2924 19 00 | 58 | <i>N,N</i> -Dimethylacrylamide (CAS RN 2680-03-7) with a purity by weight of 97 % or more | 0 % | - | 31.12.2026 |
| 0.6266 | ex 2924 29 70 | 59 | 2-(Trifluoromethyl)benzamide (CAS RN 360-64-5) with a purity by weight of 98 % or more | 0 % | - | 31.12.2029 |
| 0.3526 | ex 2925 11 00 | 40 | 1,2-Benzisothiazol-3(2 <i>H</i>)-one 1,1-dioxide (CAS RN 81-07-2) or its sodium salt (CAS RN 128-44-9) or its sodium salt dihydrate (CAS RN 6155-57-3) with a purity by weight of 98 % or more | 0 % | - | 31.12.2029 |
| 0.2661 | ex 2928 00 90 | 73 | 3,3'-Bis(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)- <i>N,N'</i> -bipropionamide (CAS RN 32687-78-8) with a purity by weight of 97 % or more | 0 % | - | 31.12.2029 |
| 0.5918 | ex 2928 00 90 | 78 | Aminoguanidinium hydrogen carbonate (CAS RN 2582-30-1) with a purity by weight of 99 % or more | 0 % | - | 31.12.2029 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|--|
| 0.8701 | ex 2929 90 90 | 80 | Wet paste or powder — with a content by weight of <i>N',N''</i> -[(2 <i>S</i> ,3 <i>E</i> ,5 <i>S</i>)-1,6-diphenylhex-3-ene-2,5-diyl]bis(<i>N,N</i> -dimethylsulfuric diamide) (CAS RN 1247119-27-2) of 70 % or more, — with a content by weight of water of not more than 30 % — and with a dry weight purity of <i>N',N''</i> -[(2 <i>S</i> ,3 <i>E</i> ,5 <i>S</i>)-1,6-diphenylhex-3-ene-2,5-diyl]bis(<i>N,N</i> -dimethylsulfuric diamide) (CAS RN 1247119-27-2) of 90 % or more | 0 % | - | 31.12.2029 |
| 0.7464 | ex 2933 69 80 | 48 | 2-(4,6-Bis-(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6) with a purity by weight of 98 % or more | 0 % | - | 31.12.2029 |
| 0.8054 | ex 2933 99 80 | 76 | 2-Methylindoline (CAS RN 6872-06-6) with a purity by weight of 98 % or more | 0 % | - | 31.12.2026 |
| 0.4942 | ex 2934 99 90 | 47 | 2,4-Diethyl-9 <i>H</i> -thioxanthen-9-one (CAS RN 82799-44-8) with a purity by weight of 97 % or more | 0 % | - | 31.12.2030 |
| 0.8830 | ex 3809 91 00 | 30 | Aqueous antimony pentoxide mixture containing by weight: — 46 % or more but not more than 55 % of antimony pentoxide (CAS RN 1314-60-9), and — 1 % or more but not more than 10 % of triethanolamine (CAS RN 102-71-6), or — 1 % or more but not more than 10 % of triethanolamine phosphate (CAS RN 10017-56-8) | 0 % | - | 31.12.2029 |
| 0.3448 | ex 3811 21 00 ex 3811 90 00 | 38 60 | Solution of mineral oils (CAS RN 64742-52-5, 64742-53-6, 64742-56-9 or blends thereof) containing by weight: — 25 % or more but not more than 55 % of the barium, calcium, magnesium or zinc salt of dinonylnaphthylsulfonic acid (CAS RN 25619-56-1, 28015-99-8, 28016-00-4, or 57855-77-3) — whether or not, not more than 25 % of the barium, calcium, magnesium or zinc salt of a mixture of C3-C24 carboxylic acids (CAS RN 68990-37-4) | 0 % | - | 31.12.2029 |
| 0.2800 | ex 3815 12 00 | 50 | Catalyst in the form of granules, wheels or ring-shaped structures — of a diameter of 3 mm or more, but not exceeding 10 mm, — containing 8 % or more but not more than 40 % by weight of silver — on a carrier based on aluminium oxide, — with one or more promoters | 0 % | - | 31.12.2029 |
| 0.2783 | ex 3815 90 90 | 60 | Dinonylnaphthalenedisulfonic acid (CAS RN 60223-95-2) with a content by weight of 50 % or more but not more than 65 %, in the form of a solution in isobutanol (CAS RN 78-83-1) | 0 % | - | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---|--|---|-------------------------|--------------------|--|
| 0.6672 | ex 3906 90 90 | 28 | Mixture containing by weight: — 80 % or more but not more than 90 % of a core shell polymer of butyl acrylate, ethyl acrylate, methyl-acrylate and allyl methacrylate (CAS RN 73026-23-0) and — 10 % or more but not more than 20 % of a copolymer of methyl methacrylate and ethyl acrylate (CAS RN 9010-88-2) | 0 % | - | 31.12.2030 |
| 0.5507 | ex 3919 90 80 | 58 | Biaxially-oriented film of poly(methyl methacrylate), with a thickness of 20 µm or more but not more than 90 µm, covered on one side with an adhesive layer and a release sheet | 0 % | - | 31.12.2029 |
| 0.7949 | ex 3920 61 00 | 40 | Extruded thermoplastic foils or films of polycarbonate with: — matt surface texture on both sides — a thickness of more than 50 µm but not more than 200 µm, — a width of 800 mm or more, but not more than 1 500 mm, and — a length of 300 m or more, but not more 2500 m for use in the production of retroreflective products ⁽¹⁾ | 0 % | - | 31.12.2030 |
| 0.7196 | ex 3926 90 97 | 77 | Silicone decoupling ring with an inner diameter of 13,2 mm or more but no more than 17,2 mm, in immediate packings of 2 500 pieces or more, of a kind used in car parking aid sensor systems | 0 % | p/st | 31.12.2026 |
| 0.8024 | ex 5911 40 00 | 10 | Non-wovens, consisting of poly(ethylene terephthalate) spun bonded media: — in the piece, cut to length or simply cut to rectangular (including square) shape, — of weight of 160 g/m ² or more but not more than 300 g/m ² , — with a filtration efficiency of class L or better (according to DIN 60335-2-69), — pleatable, with or without following treatments: — a coating or covering with polytetrafluoroethylene (PTFE), — a coating with aluminium particles, — a coating of phosphorous based flame retardants, — a nano fiber coating of a polyamide, a polyurethane or a fluorine-containing polymer — an expanded polytetrafluoroethylene (ePTFE) membrane | 0 % | m ² | 31.12.2029 |
| 0.5024 | ex 8301 60 00 ex 8419 90 85 ex 8479 90 70 ex 8481 90 00 ex 8485 90 90 ex 8503 00 98 ex 8515 90 80 ex 8537 10 98 ex 8538 90 99 ex 8708 99 10 ex 8708 99 97 | 30 40 30 50 30 43 40 55 70 55 22 | Silicone or plastic keyboards, comprising: — parts of common metal, and — whether or not comprising parts of plastic, — epoxy resin reinforced with fiberglass or wood, — whether or not printed or surface-treated, — with or without electrical conductors, — with or without a membrane bonded to the keyboard, — with or without mono or multilayer protective film | 0 % | p/st | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---|----------------|---|-------------------------|--------------------|--|
| 0.8818 | ex 8406 81 00 | 10 | Industrial steam turbine with: — an output of more than 40 MW but not more than 90 MW, — designed for a pressure of not more than 165 bar and a temperature of not more than 565 °C, — equipped with individually controlled single or double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar | 0 % | - | 31.12.2029 |
| 0.8148 | ex 8412 90 70 | 20 | Bedplate made of solution strengthened ductile iron castings (SSDI), for anchoring and aligning the drive train (gearbox, pedestal bearing, rotor shaft) of a wind turbine with: — a length of 3,5 m or more but not more than 4,5 m, — a width of 2 m or more but not more than 4,2 m, — a height of 1 m or more, but not more than 1,3 m, — a weight of 11 tons or more but not more than 21,5 tons, — mounting bores for yawdrive, — a mounting flange for gearbox support, — drivetrain mount, — different screw sockets | 0 % | p/st | 31.12.2027 |
| 0.8856 | ex 8418 99 90 | 80 | An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators: — measuring 337 x 237 x 17 mm or more, but not more than 868 x 399 x 78 mm, — with a total weight of a set of 236 g or more, but not more than 1 750 g, — with a fixed sensor, — with or without noise absorber, — with 2, 5 or 7 control and power connection pins terminated with sensor temperature type of socket, with or without heater and fuse type of socket, for use in the manufacture of products of subheadings 8418 10, 8418 21, 8418 40 (1) | 0 % | - | 31.12.2029 |
| 0.4855 | ex 8501 33 90 ex 8501 40 80 ex 8501 53 50 | 30 50 10 | Electric drive for motor vehicles, with an output of not more than 315 kW: — with an AC or DC motor with or without transmission, — with or without power electronics | 0 % | - | 31.12.2026 |
| 0.4450 | ex 8504 31 80 | 30 | Transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters and goods of heading 8537 (1) | 0 % | - | 31.12.2029 |
| 0.8660 | ex 8507 60 00 | 26 | Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with: — a length of 670 mm or more, but not more than 882 mm, — a width of 390 mm or more, but not more than 655 mm, — a height of 110 mm or more, but not more than 155 mm, — a weight of 60 kg or more, but not more than 165 kg, and — a power of 11 300 Wh or more, but not more than 29 360 Wh | 1.3 % | - | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|--|
| 0.6753 | ex 8507 60 00 | 77 | Lithium-ion rechargeable batteries, with: — a length of 700 mm or more, but not more than 2 820 mm, — a width of 935 mm or more, but not more than 1 660 mm, — a height of 85 mm or more, but not more than 700 mm, — a weight of 250 kg or more, but not more than 700 kg, — a power of not more than 175 kWh, — a nominal voltage of 320 V or more, but not more than 430 V for use in the manufacture of vehicles of subheadings 8701 to 8705 (1) | 1.3 % | - | 31.12.2026 |
| 0.8841 | ex 8537 10 91 | 75 | Printed circuit board equipped with a microcontroller for operating and/or control purposes — with or without operating components, signal components and display, — for operating voltages of 5V DC or more but not more than 24V DC or 220V AC or more but not more than 400V AC, — with or without housing for use in the manufacture of household appliances of subheadings 7321 11, 8414 60, 8418 10, 8418 21, 8418 29, 8418 40, 8422 11, 8450 11, 8450 12, 8450 19, 8450 20, 8451 21, 8451 29, 8516 60 (1) | 0 % | - | 31.12.2029 |
| 0.6377 | ex 8544 30 00 ex 8544 42 90 | 53 75 | Electrical wiring harness or cable for the steering system: — with a rated voltage of 12 V, — fitted with connectors on both ends or/and with special adapter providing sealing and anti-rotation feature, — with or without plastic anchoring jaws for mounting the steering gear housing of motor vehicles, for use in the manufacture of power steering systems for motor vehicles (1) | 0 % | p/st | 31.12.2029 |
| 0.8292 | ex 8708 95 99 | 50 | Airbag inflator containing pyrotechnics, whether or not cold gas, as propellant for safety airbags of vehicles, in each individual consignment of 1 000 pieces or more | 0 % | p/st | 31.12.2026 |
| 0.6572 | ex 9002 11 00 | 85 | Lens with — a horizontal field of view of 20° or more, but not more than 220°, — a focal length of 1.16 mm or more, but not more than 20 mm, — a relative aperture of f/1.2 or more, but not more than f/4, and — a diameter of 5 mm or more, but not more than 40 mm, for use in the manufacture of CMOS vehicle-mounted cameras or IP network cameras (1) | 0 % | - | 31.12.2029 |

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.;

(3) the following entries are inserted according to the numerical order of the CN and TARIC codes in the second and third columns:

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|--|
| 0.9085 | ex 1515 60 99 | 20 | Microbial oil, refined or semi-refined, but not chemically modified, containing by weight in the form of triglycerides: — 35 % or more but not more than 70 % of arachidonic acid — not more than 3 % by weight of docosahexaenoic acid | 0 % | - | 31.12.2030 |
| 0.9064 | ex 2904 99 00 | 75 | Trifluoromethanesulfonic acid (CAS RN 1493-13-6) with a purity by weight of 99 % or more | 0 % | - | 31.12.2030 |
| 0.9088 | ex 2905 29 90 | 50 | Prop-2-yn-1-ol (CAS RN 107-19-7) with a purity by weight of 99 % or more | 0 % | - | 31.12.2030 |
| 0.9071 | ex 2921 43 00 | 45 | α,α,α -Trifluoro- <i>o</i> -toluidine (CAS RN 88-17-5) with a purity by weight of 98 % or more | 0 % | - | 31.12.2030 |
| 0.9016 | ex 2922 29 00 | 53 | <i>m</i> -Anisidine (CAS RN 536-90-3) with a purity by weight of 95 % or more | 0 % | - | 31.12.2030 |
| 0.9012 | ex 2924 29 70 | 44 | 4-(2,2-Diethoxyacetyl)-3,5-difluoro- <i>N</i> -methylbenzamide (CAS RN 3089027-90-4) with a purity by weight of 95 % or more | 0 % | - | 31.12.2030 |
| 0.9010 | ex 2928 00 90 | 68 | Ethyl hydrazinoacetate hydrochloride (CAS RN 6945-92-2) with a purity by weight of 98 % or more | 0 % | - | 31.12.2030 |
| 0.9006 | ex 2930 90 95 | 22 | 4,4,5,5,5-Pentafluoropentyl carbamimidothioate—methanesulfonate (1:1) (CAS RN 1107606-68-7) with a purity by weight of 99 % or more | 0 % | - | 31.12.2030 |
| 0.9011 | ex 2930 90 95 | 24 | Trimethyloxosulfonium chloride (CAS RN 5034-06-0) with a purity by weight of 98 % or more | 0 % | - | 31.12.2030 |
| 0.9004 | ex 2931 90 00 | 21 | (2-Fluoro-4-phenoxyphenyl)boronic acid (CAS RN 1414356-30-1) with a purity by weight of 95 % or more | 0 % | - | 31.12.2030 |
| 0.9013 | ex 2932 19 00 | 38 | (2,2-Diphenyltetrahydrofuran-3-yl)methanol (CAS RN 93651-75-3) with a purity by weight of 98 % or more | 0 % | - | 31.12.2030 |
| 0.9015 | ex 2933 19 90 | 78 | 3-(3-Methyl-5-oxo-4,5-dihydro-1 <i>H</i> -pyrazol-1-yl)benzenesulfonic acid (CAS RN 119-17-5) with a purity by weight of 95 % or more | 0 % | - | 31.12.2030 |
| 0.9075 | ex 2933 19 90 | 83 | Isomeric mixture containing by weight 97 % or more of the two isomers — 2-(3,4-Dimethyl-1 <i>H</i> -pyrazol-1-yl)succinic acid and — 2-(4,5-Dimethyl-1 <i>H</i> -pyrazol-1-yl)succinic acid (CAS RN 2241455-89-8) | 0 % | - | 31.12.2030 |
| 0.9008 | ex 2933 39 99 | 19 | 5-Chloro-1-(4-piperidyl)-1 <i>H</i> -benzimidazol-2(3 <i>H</i>)-one (CAS RN 53786-28-0) with a purity by weight of 99 % or more | 0 % | - | 31.12.2030 |
| 0.9060 | ex 2933 39 99 | 94 | Cyantraniliprole (ISO) (CAS RN 736994-63-1) with a purity by weight of 90 % or more | 0 % | - | 31.12.2030 |
| 0.8997 | ex 2933 59 95 | 35 | 3-Iodo-1 <i>H</i> -pyrazolo[3,4- <i>d</i>]pyrimidin-4-amine (CAS RN 151266-23-8) with a purity by weight of 98 % or more | 0 % | - | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|--|
| 0.9061 | ex 2933 59 95 | 40 | Pirimiphos-methyl (ISO) (CAS RN 29232-93-7) with a purity by weight of 90 % or more | 0 % | - | 31.12.2030 |
| 0.9058 | ex 2933 69 80 | 38 | Tris([1,1'-biphenyl]-4-yl)-1,3,5-triazine (CAS RN 31274-51-8) with a purity by weight of 97 % or more | 0 % | - | 31.12.2030 |
| 0.9009 | ex 2933 99 80 | 83 | 1-(3-Chloropropyl)-1,3-dihydro-2H-benzimidazol-2-one (CAS RN 62780-89-6) with a purity by weight of 97 % or more | 0 % | - | 31.12.2030 |
| 0.8994 | ex 2933 99 80 | 84 | Allyl (2S,4S)-4-benzoylsulfanyl-2-(dimethylcarbamoyl)pyrrolidine-1-carboxylate (CAS RN 141818-73-7) with a purity by weight of 96 % or more | 0 % | - | 31.12.2030 |
| 0.8996 | ex 2934 99 90 | 32 | (6R,7R)-Benzhydryl 3-hydroxy-8-oxo-7-(2-phenylacetamido)-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylate (CAS RN 54639-48-4) with a purity by weight of 95 % or more | 0 % | - | 31.12.2030 |
| 0.9005 | ex 2934 99 90 | 34 | Benzyl 4-(oxetan-3-yl)piperazine-1-carboxylate (CAS RN 1254115-22-4) with a purity by weight of 99 % or more | 0 % | - | 31.12.2030 |
| 0.9007 | ex 2934 99 90 | 36 | Nadide phosphate (INNM) disodium salt (CAS RN 24292-60-2) with a purity by weight of 97 % or more | 0 % | - | 31.12.2030 |
| 0.8993 | ex 2934 99 90 | 46 | (6R-trans)-7-Amino-8-oxo-3-[[[1,2,5,6-tetrahydro-2-methyl-5,6-dioxo-1,2,4-triazin-3-yl]thio]methyl]-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 58909-56-1) with a purity by weight of 97 % or more | 0 % | - | 31.12.2030 |
| 0.9056 | ex 3204 17 00 | 32 | Colourant C.I. Pigment Violet 23 (CAS RN 215247-95-3) and preparations based thereon with a colourant C.I. Pigment Violet 23 content of 70 % or more by weight | 0 % | - | 31.12.2030 |
| 0.9074 | ex 3810 10 00 | 10 | Tin or zinc based, halide free, surface mount technology processing solder paste: — with metal contents of 87,5 % or more, but not more than 90,1 % by weight, — with an alloy solidus temperature of 210°C or more, — with a viscosity of 178 Pa·s or more, but not more than 235 Pa·s, — with a particle size of 40 µm or less, — with a silver content either of 3,15 % or more, but not more than 3,5 % by weight for tin based paste or of 0,25 % or more, but not more than 0,28 % by weight for zinc based paste, — with or without bismuth content of 2,55 % or more, but not more than 2,71 % by weight, — with or without copper content of 0,6 % or more, but not more than 0,7 % by weight | 0 % | - | 31.12.2030 |
| 0.9073 | ex 3815 12 00 | 40 | Catalyst used to obtain paraxylene and orthoxylene by isomerization of methaxylene containing by weight: — 60 % or more but not more than 95 % of aluminum oxide (CAS RN 1344-28-1), — 5 % or more but not more than 15 % of aluminosilicate (CAS RN 1327-36-2), — not more than 2 % of platinum (CAS RN 7440-06-4), — not more than 2 % aluminum chloride hydroxide (CAS RN 12042-91-0), — not more than 0,2 % of hydrogen sulfide (CAS RN 7783-06-4) | 0 % | - | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|--|
| 0.9086 | ex 3815 19 90 | 33 | Catalyst, in powder form, consisting of a mixture of metal oxides fixed to a silicon dioxide support, with a total content by weight of molybdenum, bismuth and iron of 20 % or more but not more than 50 %, for use in the manufacture of acrylonitrile (1) | 0 % | - | 31.12.2030 |
| 0.9062 | ex 3824 99 96 | 38 | Low outgassing thermally conductive silicone paste: — with thermal conductivity when cured of 3,45 W/(m·K) or more but not more than 3,55 W/(m·K), — with continuous use temperature minimum range from -60 °C to 200 °C, — with heat capacity when cured of 0,75 J/g·K or more but not more than 0,85 J/g·K, — with volume resistivity when cured of 1010 Ω·m or more, — packaged in containers of 30 kg or more | 0 % | - | 31.12.2030 |
| 0.8999 | ex 3902 90 90 | 63 | Hydrogenated poly(1-octene) (CAS RN 70693-43-5) | 0 % | - | 31.12.2030 |
| 0.9078 | ex 3907 29 20 | 63 | Preparation containing by weight — 5 % or more but not more than 15 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6) and — 85 % or more but not more than 95 % of oxirane, 2-methyl-, polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazonyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5) | 0 % | - | 31.12.2030 |
| 0.9079 | ex 3907 29 20 | 65 | Preparation containing by weight — 40 % or more but not more than 60 % of oxirane, 2-methyl-, polymer with oxirane, ether with 2,2-[[3-methyl-4-[(4-methyl-2-benzothiazolyl)azo]phenyl]imino]bis[ethanol] (2:1) (CAS RN 229306-55-2) and — 40 % or more but not more than 60 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6) | 0 % | - | 31.12.2030 |
| 0.9077 | ex 3907 29 20 | 68 | Preparation containing by weight — 90 % or more but not more than 99 % of oxirane, 2-methyl-, polymer with oxirane, ether with ethyl 3-(4-(bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3) and — 1 % or more but not more than 10 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6) | 0 % | - | 31.12.2030 |
| 0.9081 | ex 3907 29 20 | 70 | Preparation containing by weight — 50 % or more but not more than 70 % of oxirane, methyl-polymer with oxirane, ether with bis(4-[bis(2-hydroxyethyl)amino]phenyl) (2-sulfophenyl)methyl (4:1), monosodium salt block (CAS RN 126042-89-5) and — 30 % or more but not more than 50 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6) | 0 % | - | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|--|
| 0.9082 | ex 3907 29 20 | 73 | Preparation containing by weight of — 23 % or more but not more than 36 % of oxirane, 2-methyl-,polymer with oxirane, ether with bis(4-(bis(2-hydroxyethyl)amino)phenyl)(2-sulfophenyl)methyl (4:1), monosodium salt, block (CAS RN 126042-89-5), — 4 % or more but not more than 20 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6), — 25 % or more but not more than 30 % of oxirane, 2-methyl-,polymer with oxirane, ether with 2,2'-((3-methyl-4-((4-methyl-2-benzothiazolyl)azo)phenyl)imino)bis(ethanol)(2:1) (CAS RN 229306-55-2), — 5 % or more but not more than 10 % of oxirane, 2-methyl-,polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazanyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5) and — 15 % or more but not more than 25 % of oxirane, 2-methyl-,polymer with oxirane, ether with ethyl 3-(4-bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3) | 0 % | - | 31.12.2030 |
| 0.9080 | ex 3907 29 20 | 75 | Preparation containing by weight — 60 % or more but not more than 80 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 2,2',2'',2'''-(sulfonylbis(4,1-phenylene)-2,1-diazenediyl(3-methyl-4,1-phenylene)nitrilo))tetrakis(ethanol) (4:1) (CAS RN 927432-39-1) and — 20 % or more but not more than 40 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6) | 0 % | - | 31.12.2030 |
| 0.9001 | ex 3919 90 80 | 57 | Self-adhesive polycarbonate film, printed, whether or not arched, with: — a thickness of 0,3 mm or more, but not more than 0,4 mm, — minimum dimensions of 63 mm x 15 mm, — maximum dimensions of 278 mm x 117 mm, — a weight of not more than 5 g per piece, intended for integration into combined instrument panels of passenger cars | 0 % | - | 31.12.2030 |
| 0.9057 | ex 3920 62 19 | 70 | Poly(ethylene terephthalate) film in rolls with: — a thickness of 35 µm or more, but not more than 75 µm, — a tensile strength of 40 MPa or more in the machine direction (MD) and 200 MPa or more in the transverse direction (TD), — an elongation at break of 400 % or more in MD and 30 % or more in TD, — a heat shrinkage (in water at 90 °C/10s) in MD of 0,49 % or more, but not more than 0,51 %, — a dynamic heat shrinkage (between 55 °C and 70 °C) in TD of not more than 20 percentage points, — a light transmittance of 85 % or more, — a haze ratio of not more than 6 %, — a surface tension of 38 mN/m or more, — a density of 1,30 g/cm ³ or more, but not more than 1,34 g/cm ³ , — a shelf life declared by the manufacturer of not less than 12 months | 0 % | - | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|--|
| 0.9055 | ex 3921 19 00 | 53 | Sheets of closed-cell silicone foam with: — a thickness of 2,0 mm or more but not more than 4,8 mm, — a thermal insulation of more than 0,25 Km ² /W but not more than 0,4 Km ² /W (according to ASTM-C518) — a dielectric strength of more than 3,0 Kv/mm but not more than 3,8 Kv/mm (according to ASTM- D149) | 0 % | - | 31.12.2030 |
| 0.9048 | ex 5401 10 14 | 10 | Core yarn of high tenacity polyester filament surrounded by polyester staple fibres: — with a twist of 410 TPM or more but not more than 1200 TPM, — with a linear density of 200 dtex or more but not more than 1500 dtex, — with an average tenacity of 46 cN/tex or more, — with an elongation at break of 13 % or more but not more than 23 %, — wound on a perforated dyeing tube, — with a weight, including tube, of 900 g or more | 0 % | - | 31.12.2030 |
| 0.9003 | ex 5402 20 00 | 07 | High tenacity polyester multifilament yarn: — with final twist in Z direction; — with a linear density of 100 dtex or more, but not more than 4000 dtex — with an average minimum tenacity of 64 cN/tex; — with an elongation at break of 12 % or more, but not more than 28 %; — with a shrinkage in 98 °C of 0 % or more, but not more than 3,5 %; — wound on the perforated dyeing tube with 0,9 kg of yarn or more ready for dyeing | 0 % | - | 31.12.2030 |
| 0.9063 | ex 5503 90 00 | 40 | Staple fibres with a poly(ethylene terephthalate) core fully encapsulated by polyethylene with: — a linear density of 0,60 dtex or more but not more than 1,60 dtex, — a staple fibre length of 37 mm or more but not more than 44 mm, — an elongation at break of 80 % or more, — a tenacity of 1 cN/dtex or more | 0 % | - | 31.12.2030 |
| 0.8939 | ex 5603 94 80 | 50 | Needle-punched spunbond nonwovens, consisting of polyamide fibres individually coated with polyvinylalcohol, containing by weight 20 % or more but not more than 40 % of polyvinylalcohol weighing 400 g/m ² or more | 0 % | - | 31.12.2030 |
| 0.9053 | ex 6804 21 00 | 50 | Wheels suitable for grinding, rounding, polishing, aligning or cutting: — composed of metal base and agglomerated synthetic or natural diamonds, — whether or not containing a hole in the centre, — with an external diameter not more than 870 mm, for machines for the manufacture of semiconductor wafers (1) | 0 % | - | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|--|
| 0.8998 | ex 6814 10 00 | 20 | Phlogopite mica tape bonded with silicone resin to a glass fabric reinforced polyethylene film, — with a thickness of 0,10 mm or more but not more than 1,60 mm, — with a width of 500 mm or more but not more than 1200 mm, — a mica content of 80 g/m ² or more but not more than 165 g/m ² , — a tensile strength of 110 N/cm or more but not more than 130 N/cm | 0 % | - | 31.12.2030 |
| 0.9059 | ex 7002 20 90 | 10 | Cylindrical shaped glass preforms of high-purity silica glass (quartz): — with an optical core made of germanium-doped silica glass (quartz), intended for the production of low-loss optical fiber: — with a length of not more than 2500 mm, — with a diameter of 115 mm or more but not more than 139 mm, — on one side with a conical end — on the other side with a handle with a diameter of 25,4 mm, coated at the end with aluminium oxide | 0 % | - | 31.12.2030 |
| 0.9054 | ex 7019 61 00 | 60 | Flexible prepreg in sheets or rolls, — of modified epoxy resin with embedded glass fabric, — without halogenated flame retardants — with a TMA glass transition of 145 °C or more but not more than 200 °C (ASTM E1545) — specified according to IPC-4101/128, 130, 153 or 154 | 0 % | - | 31.12.2030 |
| 0.9087 | ex 7410 21 00 | 65 | Sheets or Plates — consisting of at least one layer of fiberglass fabric impregnated with modified epoxy resin, without the use of halogenated flame retardants, — covered on one or both sides with copper foil with a thickness of 0,15 mm or less, — and with a TG of 145°C or more but not more than 280°C according to TMA, in agreement with IPC-4101/128 or 4101/130 or IPC-4101/153 or 4101/154 | 0 % | - | 31.12.2030 |
| 0.9049 | ex 8110 90 00 | 10 | Antimony-Beryllium pellets containing by weight : — 20 % or more but not more than 25 % of beryllium (CAS 7440-41-7) — 77 % or more but not more than 83 % of antimony (CAS 7440-36-0) | 0 % | - | 31.12.2030 |
| 0.9018 | ex 8414 30 20 | 60 | Hermetic compressor for R290 refrigerant for the production of refrigerators and freezers: — with a power not exceeding 0.4 kW, — pre-filled with lubricant from 190 ml to 210 ml, — suction and processing pipe inner diameter from 6.40 mm to 6.60 mm, — discharge pipe inner diameter from 4.80 mm to 5.00 mm, — driven by a brushless DC motor, — cooling capacity from 340 to 360 W at ASHRAE LBP 3000 rpm, — displacement from 6.5 cm ³ to 7.5 cm ³ , — speed range from 1,600 rpm to 4,200 rpm (1) | 0 % | - | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|--|
| 0.9045 | ex 8414 59 35 | 50 | DC motor centrifugal fan with: — a nominal voltage of 8 V or more, but not more than 13 V, — a nominal maximum speed of 1400 rpm or more, but not more than 1950 rpm, — a horizontal or vertical position of the fan blades shaft, — a boosting time of not more than 10 seconds, — a cable with a length of 30 cm or more, but not more than 50 cm, with RAST 2,5 connector, — a nominal power of 0,7 W or more, but not more than 3,5 W, — a tacho or feedback signal to monitor the speed | 0 % | p/st | 31.12.2030 |
| 0.9044 | ex 8418 99 90 | 70 | Household appliances condenser, being a type of heat exchanger, made entirely of aluminium A3102, A3003, A4045 or A4343, consisting of two vertical pipes and arranged horizontally between them 16 parallel flat tubes with fins, with: — one vertical pipe with inlet and outlet tubes, — a width of 297 mm or more, but not more than 373 mm, — a height of 154 mm or more, but not more than 158 mm, — a depth of 17 mm or more, but not more than 23 mm, — a flatness tolerance of less than 2 mm for the fin pack within the condenser core, — a weight of 224 g or more, but not more than 283 g | 0 % | - | 31.12.2030 |
| 0.9023 | ex 8483 30 80 | 30 | Commutator end shield (bearing housing with plain shaft bearing) for starter motors of passenger cars and commercial vehicles — produced with high pressure precision die casting technology, — made of aluminium alloy (EN AC-46000 or EN AC-46000 S, according to the DIN EN 1706 and GB/T 16116 standards), — with sintered plain bearing | 0 % | - | 31.12.2030 |
| 0.9040 | ex 8483 50 80 | 50 | Metal spun single or double pulley: — made of DC03 steel or similar non alloy steel or free cutting steel, — with a pitch diameter of 67 mm or more but not more than 145 mm, — with an inner hole designed for bearing mounting or key mounting | 0 % | - | 31.12.2030 |
| 0.9039 | ex 8483 50 80 | 60 | Metal spun triple pulley: — made of DC03 steel or similar non-alloy steel or free cutting steel, — with a pitch diameter of 60 mm or more, but not more than 130 mm, — with an inner hole designed for bearing mounting | 0 % | - | 31.12.2030 |
| 0.9025 | ex 8483 60 80 | 20 | Overrunning clutch for passenger car and commercial vehicle starter motors with: — a total length of 49,4 mm or more but not more than 210 mm, — a starter motor pinion with 9 or more but not more than 16 teeth | 0 % | - | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|--|
| 0.9037 | ex 8501 52 20 | 55 | Brushless synchronous alternating current electric motors with permanent magnets, with: <ul style="list-style-type: none"> — an output power of 1000 W or more, but not more than 1400 W, — a rotor containing 8 poles, generated by permanent magnets composed mainly of praseodymium-neodymium-iron-boron (GB/T 13560-2017 standard), enclosed in a stainless steel cover, — a motor magnet shaft end outer diameter of 10,001 mm or more, but not more than 10,007 mm, — motor terminals located across the 37,00 mm radius and separated by an angle of 30,00 °, — a motor housing made of ADC12 or EN AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302-2000 or EN 1706 standard), — a back electromotive force constant (Ke) of 0,0265 V-sec/rad or more, but not more than 0,0293 V-sec/rad, — a back electromotive force (EMF) harmonic order – 5th of no more than 0,4 % (of fundamental) and 7th of no more than 0,2 % (of fundamental), — a synchronous inductance of 33,49 µH or more, but not more than 37,01 µH, — a cogging torque of not more than 15 mNm, — a friction torque in ambient temperature of not more than 20 mNm, — a maximum motor operation temperature of not more than 200 °C, — with or without a spline on the motor shaft | 0 % | p/st | 31.12.2030 |
| 0.9020 | ex 8503 00 20 | 20 | Plated steel core of the electric motor rotor of electric air conditioning compressors for motor vehicles: <ul style="list-style-type: none"> — with an outer diameter of 65 mm or more but not more than 80 mm, — with an inner diameter of 15 mm or more but not more than 25 mm, — with a height of 30 mm or more but not more than 45 mm, — with a weight of 0,5 kg or more but not more than 0,8 kg, — without windings | 0 % | - | 31.12.2030 |
| 0.9019 | ex 8503 00 20 | 30 | Plated steel core of the electric motor stator of electric air conditioning compressors for motor vehicles: <ul style="list-style-type: none"> — with an outer diameter of 90 mm or more but not more than 120 mm, — with an inner diameter of 65 mm or more but not more than 80 mm, — with a height of 30 mm or more but not more than 45 mm, — with a weight of 0,7 kg or more but not more than 1,2 kg, — without windings | 0 % | - | 31.12.2030 |
| 0.9021 | ex 8503 00 98 | 45 | Armature for the electric motor in starter motors of passenger cars and commercial vehicles with: <ul style="list-style-type: none"> — an outer diameter of 52 mm or more but not more than 80 mm, — a commutator copper wire diameter of 2 mm or more but not more than 4 mm | 0 % | - | 31.12.2030 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|--|
| 0.9026 | ex 8511 90 00 | 20 | Drive end shield for starter motors and alternators of passenger cars and commercial vehicles — produced with high pressure precision die casting technology, — made of aluminium alloy (EN 1706 grade AC-47100 or AC-47100 S or AC-46000 or AC-46000 S or AC-44300), — whether or not with bearing | 0 % | - | 31.12.2030 |
| 0.9022 | ex 8511 90 00 | 30 | Commutator for passenger car and commercial vehicle starter motors — with a length of 27,7 mm or more but not more than 44,6 mm, — with umbrella or drum design | 0 % | - | 31.12.2030 |
| 0.9043 | ex 8516 80 80 | 10 | Electric heating resistor with a triple loop design: — mainly made of AISI 316L stainless steel, — with a rated voltage of 230V, — with a rated power of 2000W, — with a total heating element length of 217 mm or more, but not more than 223 mm, — with a heating element working length of 169,5 mm or more, but not more than 174,5 mm, — with a mounting flange diameter of 28 mm or more, but not more than 32 mm, — with a heating element bending radius of 10,75 mm, — equipped with thermal fuses, — without a built-in NTC sensor, — with nickel plated terminal pin and connector | 0 % | - | 31.12.2030 |
| 0.9014 | ex 8544 30 00 | 23 | High-voltage single-core battery supply cable fitted with: — a high-voltage connector, — a metal flat lug with an eyelet in a plastic housing, — three or more plastic mounting clips for use in the manufacture of rechargeable batteries for hybrid and electric vehicles (1) | 0 % | - | 31.12.2030 |
| 0.9000 | ex 8544 30 00 | 33 | Wiring harness for transmitting safety parameters from battery modules fitted with: — input and output connectors, — three or more plastic mounting clips for use in the manufacture of rechargeable batteries for hybrid and electric vehicles (1) | 0 % | - | 31.12.2030 |
| 0.9002 | ex 8544 30 00 | 43 | High voltage battery cable assembly, comprising: — a single core high voltage cable terminated with a flat lug, — a safety fuse for an electric current of 10 A or more but not more than 400 A, — a flat copper conductor with surface insulation terminated with a flat lug, — three or more plastic clips for attachment for use in the manufacture of rechargeable batteries for hybrid and electric vehicles (1) | 0 % | - | 31.12.2030 |
| 0.9027 | ex 8547 90 00 | 10 | Li-ion battery module component made of mica for fire protection, with a specially designed shape for the top and sides with: — a length of 480.0 or more but not more than 630.0 mm, — a width of 78.0 or more but not more than 233.0 mm and — a thickness of 0.75 or more but not more than 2.50 mm | 1.85 % | - | 31.12.2026 |

| Serial Number | CN code | TARIC | Description | Rate of autonomous duty | Supplementary Unit | Deadline foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|--|
| 0.9038 | ex 8548 00 90 | 45 | Electromagnetic Interference filter designed to eliminate conducted electromagnetic interference from a power line, — with a rated voltage of 250 V AC, — with a rated current of not more than 15 A, — with an operating frequency of 50/60 Hz, — with a dielectric strength of 1500V AC for 1 minute, — containing a bleeder resistor with a resistance of 470 kΩ, — containing three varistors: one with rated voltage of 680 V, one of 910 V and one of 1800 V, each ±10 %, — mounted with an M8 screw with an average breaking force of 93 kgf/cm | 0 % | - | 31.12.2030 |
| 0.9033 | ex 8708 94 99 | 80 | Blank assembly worm gear, consisting of a hub of carbon steel (GB/T 699 grade 25 or DIN EN 10277 grade 11SMn30) and a ring of cast polyamide 6/12 with: — an outer diameter of 97,35 mm or more, but not more than 102,65 mm, — an inner diameter of 27,91 mm or more, but not more than 27,93 mm, — a height of the hub of 11,75 mm or more, but not more than 12,00 mm, — an overall height of 16,00 mm or more, but not more than 18,00 mm | 0 % | - | 31.12.2030 |
| 0.9029 | ex 8708 99 97 | 27 | Inner pole electromagnet core used in Magneto-Rheological engine mounts to reduce shocks and for isolation and damping in passenger cars: — of a powder metal assembly, — with a diameter of not more than 90,95 mm, — with an overall height of 24,5 mm, — impregnated with sealant, — zinc plated | 0 % | - | 31.12.2030 |
| 0.9030 | ex 9401 99 20 | 30 | Latch seat system modules enabling seat sliding, latching and unlatching in random, independent positions along the rails: — with an integrated safety locking mechanism, — with a cassette architecture for integration with seat through screw connections, — with a housing made of a magnesium die-cast alloy, — with an anti-noise system, — interfacing with car rail systems, — without electronic control unit, — without semiconductors, — with a weight of 1475 g or more, but not more than 1619 g | 0 % | - | 31.12.2030 |

⁽¹⁾ Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.⁷.